CONVERTAMATICTM 240LX & 265LX

The *Convertamatic 240LX* and *265LX* self-propelled scrubbers are designed for easy operation. They're easy to use, easy to maintain and produce great results. You can scrub up to five hours and 55,000 square feet (5150 m²) on one charge. The curved, pivoting squeegee follows the scrub path even on sharp turns and next to walls leaving floors clean, dry and safe.

The 240LX and 265LX are built to last with ten-gauge steel body and polyethylene tanks that won't rust or corrode. Gear-case pad/brush drive is quiet and virtually maintenance free. The recovery tank has a built-in float system that automatically shuts-off the vacuum air flow, preventing vacuum motor damage.

Both models are easy to use with drive-to-thewheels which propels the machine forward and reverse. Three solution options: automatic for normal operations; off for double scrubbing; and manual override for spot cleaning. In the automatic solution mode, the scrubber evenly applies cleaning solution at a set rate. When the machine stops, so does the solution flow. So do the pads or brushes, to protect the floor. The controls are very easy...everything's automatic, solution flows, pads rotate and the *240LX* or *265LX* propel themselves. Just twist the grips and you're on your way.



Standard Features Include:

- Two Short-Trim pad holders
- Curved Squeegee



Controls are easy to use. Everything's automatic; solution flows, brushes/pads rotate and the *240LX* and *265LX* propel themselves...just twist the grips and you're on your way.



Tanks are sized for productivity and won't rust or corrode. Tough polyethylene tanks are impact resistant and lift out without removing any nuts or bolts.



Easy access to modular components that can be lifted out for service or repair. Modular components include tanks, brush drive, vac motor, front end, control handle and battery compartment.



Curved, pivoting squeegee follows scrub path, providing excellent solution pick up and leaving floors clean, dry and safe.

<u>S P E C I F I C A T I O N S</u>

••••••••••••••••••••••••••••••••••••••	
Scrubbing Path:	<i>240LX</i> — 24" (61 cm) <i>265LX</i> — 26" (66 cm)
Cleaning Rate:	240LX – 23,520 sq. ft./hour (2175 m²/hr.)* 265LX – 25,480 sq. ft./hour (2360 m²/hr.)*
Average Coverage:	<i>240LX</i> – 10,000 sq. ft./hour (929 m²/hr.) <i>265LX</i> – 11,000 sq. ft./hour (1022 m²/hr.)
Speed Control:	Electronic, fully variable from 0–196 feet per minute (0–60 m/min.), forward. Reverse is 70% of max forward speed.
Solution Tank:	17 gal. (64 l.) polyethylene
Recovery Tank:	20 gal. (76 I.) polyethylene w/auto shut-off
Squeegee:	4-sided, curved, pivot type
Squeegee Size:	<i>240LX</i> – 30.5" (77 cm) <i>265LX</i> – 36.25" (92 cm)
Motors:	Pad/Brush Drive – 1 hp (746 watt), 24 v DC Wheel Drive – .25 hp (186 watt), DC Vacuum: – .75 hp (560 watt), bypass
Pads/Brushes:	240LX – two 12" (30 cm) diameter 265LX – two 13" (33 cm) diameter
Pad/Brush Pressure:	110 lbs. (50 kg)
Pad/Brush Speed:	170 r.p.m.
Sound Level:	67 db(A)
Wheels:	8" (20 cm) soft-ride drive wheel, rear casters
Gauges:	Battery condition meter standard.
Batteries:	Either – four 6 v/244 amp hour uses 24 v/20 amp charger Or – four 6 v/305 amp hour uses 24 v/25 amp charger
Dimensions:	Length – <i>240LX</i> : 53" (135 cm) – <i>265LX</i> : 53.5" (136 cm) Width – <i>240LX</i> : 25" (63 cm) – <i>265LX</i> : 27" (69 cm) Height – 43" (109 cm) overall
Weight (either model):	Net w/o batteries: 530 lbs. (240 kg) Net w/four 6 v/244 AH battys: 817 lbs. (371 kg) Net w/four 6 v/305 AH battys: 936 lbs. (425 kg) Shipping (machine only): 605 lbs. (274 kg)

All specifications subject to change without notice.

* These figures are based on straight scrubbing time and do not take into account brush/pad overlap, obstacles, turn-about time or tank empty/refill time. Individual results may vary.

Product Part Numbers:

Model *240LX* — 393 320 Model *265LX* — 393 670



 Nilfisk-Advance, Inc.

 14600 21st Avenue North

 Plymouth, MN, 55447-3408

 www.nilfisk-advance.com

 Phone:
 800-989-2235

 Fax:
 800-989-6566

Nilfisk-Advance Canada Company 396 Watline Avenue Mississauga, Ontario, Canada, L4Z 1X2 www.nilfisk-advance.com Phone: 800-668-8400 or 905-712-3260 Fax: 800-263-5111 or 905-712-3255

©1998, Nilfisk-Advance, Inc., Form L0230A, 6/98 Printed in U.S.A.