

U
S
P
R
O
D
U
C
T
S

HHP SERIES

Portable Heated & Non-Heated Carpet Extractors

The HHP Series portable carpet extractors offer versatility, labor savings and superior cleaning results. Cleaning with high heat and pressure dramatically improves cleaning effectiveness. The HHP Series offers instant heat to 212 °F at the wand tip on all heated models and psi of 150, 75/300 or adjustable 0-300. Adjustable pressure allows you to clean carpets, fabrics and upholstery. Each machine uses our low moisture system which improves drying times. The HHP Series offers solid state circuitry, including our patented circuit locator to prevent blown circuits. It's compact enough to fit upright in your van or S.U.V. Experience the super-cleaning power of the HHP Series portable extractors.

Contact U.S. Products today for more information on the HHP Series.

Heated Carpet Extractors

HHP-300

Fully adjustable psi from 0-300, fully adjustable 212 °F, soft start 3-stage vacuum with electronic shutoff and 140" lift. 12 gallon solution and recovery tanks.

HHP-310

300/75 psi for carpet or upholstery, instant 212 °F, large 3-stage vacuum with 140" lift. 12 gallon solution and recovery tanks.

HHP-150*

150 psi, dual vac motors with patented vac manifold system, 150" lift, instant heat to 212 °F, 12 gallon solution & recovery tanks.

Non-Heated Carpet Extractors

HP310-C*

High/low pressure control system with either 300 or 75 psi, 3-stage vacuum with 140" lift, 12 gallon holding & recovery tanks.

HP150-C*

150 psi, dual 2-stage vac motors with patented vac manifold system, 150" lift, 12 gallon holding & recovery tanks.



800.440.6723

www.southeasternequipment.net



Heated & Non-Heated Carpet Extractors

HHP SERIES

Portable Heated & Non-Heated Carpet Extractors

Exclusive Features from U.S. Products

- Heater Element: In-line, after the pump for longer life and instant heat to 212 °F, lifetime warranty.
- Smart Circuit Locator: Automatically detects separate lines to eliminate blown circuits.
- Low Moisture System: Less water (combined with higher heat) means faster drying, less chance of shrinkage, and less wicking from the pad.
- Tanks & Bodies: Lightweight, rotationally molded with a lifetime warranty against cracks, leaks and dents.
- Cord Wrap: Accommodates up to 50 feet of 12/3 electrical cord.
- Solid State Circuitry: Senses temperature change in heat exchanger within 1 degree for more consistent heat at the wand tip.
- Patented Vacuum Manifold: Increases efficiency when using two vacuum motors in series.

SPECIFICATIONS:

	<u>HHP-300</u>	<u>HHP-310</u>	<u>HHP-150*</u>	<u>HP310-C*</u>	<u>HP150-C*</u>
Vacuum	7.2", 3-stage soft start vac	7.2", 3-stage	Twin 2-stage 5.7" vacs with w/vac manifold	7.2", 3-stage	Twin 2-stage 5.7" vacs with w/vac manifold
VAC Shutoff	Electronic	Ball float	Ball float	Ball float	Ball float
Pump	Positive displacement fully adjustable 0-300 psi	Positive displacement 300 psi for carpet 75 psi upholstery	Demand Pump 150 psi	Positive displacement 300 psi for carpet 75 psi upholstery	Demand Pump 150 psi
Waterlift	140"	140"	150"	140"	150"
Heat	Adjustable to 212 °F	212 °F	212 °F	No Heater	No Heater
Heater	2000 Watts	2000 Watts	2000 Watts	No Heater	No Heater
Gauge	Glycerin filled	Glycerin filled	No Gauge	Glycerin filled	No Gauge
Wand	Evolution rotationally molded, twin tip, 300 psi	Evolution rotationally molded, twin tip, 300 psi	Stainless steel, single bend, twin tip	Stainless steel, double bend, twin tip	Stainless steel, single bend, twin tip
Weight	92 lbs.	99 lbs.	88 lbs.	93 lbs.	82 lbs.

Standard Features on all HHP Models:

- Dimensions: 34.75H x 17.5W x 36.5L (inches)
- 12 gallon solution and recovery tanks
- Available in 120V and 220/240V VAC, 50/60Hz
- Cord wrap
- Large non-marking wheels
- Two handles for easy maneuverability and loading
- Warranty: Lifetime on tank and body, lifetime on heater element, 1 year parts and labor

Standard Features on Heated Models

- Smart circuit locator
- Solid state circuitry
- Low moisture system
- 15' high pressure solution line and crushproof vacuum hose
- Cords: 2 each 25' 12/3 gauge, hospital grade plug

Non-Heated Models

- 15' low pressure solution line and crushproof vacuum hose
- Single cord: 25' 12/3 gauge, hospital grade plug




800.440.6723
www.southeasternequipment.net

Heated & Non-Heated Carpet Extractors

U
S
P
R
O
D
U
C
T
S