

# EXTRACTORS

DEFINING CLEANING INNOVATION

**Advance**  
by Nilfisk-Advance

COMMERCIAL EQUIPMENT



## Advance AquaClean® 12, 15, 18 & Classic

### Self-Contained Extractor

- Available in 4 sizes for a variety of cleaning applications
- Single nozzle spray system allows for even coverage over the cleaning path
- Optional kit for hard floor scrubbing



## Advance Aquamatic Selectric™

### Self-Propelled Extractor

- Self propelling drive with four speeds for forward and reverse
- 25 gallon tank-in-tank design allows for a low profile
- 18 inch brush reverses for double scrubbing



## Advance AquaRide® SE

### Rider Sweeper Extractor

- Increases productivity up to 400% by sweeping and extracting in one pass
- Dual mode cleaning for low moisture and deep extraction
- 45 gallon solution tank with a 28 inch brush allows for high square footage per tank
- Dual rotating brushes sweep and clean both sides of the carpet
- Superior turning ability within a 63 inch radius
- One-Touch™ control panel for all scrub functions
- The operator compartment has ClearView™ sight lines
- QuickChange no tools removable deck system



## Advance AquaMax®

### Battery Operated Extractor

- 40 gallon solution tank with a 25 in cleaning path for high productivity and deep cleaning
- Dual mode cleaning for low moisture and deep extraction
- Slide out brush deck allows for edge cleaning
- Ease of maintenance with no tools removal of the brush, vacuum shoes and vacuum motors

# EXTRACTORS

DEFINING CLEANING INNOVATION



# Advance

by Nilfisk-Advance

## SPECIFICATIONS

MODELS:	AquaClean® 12	AquaClean® 15	AquaClean® 18	AquaClean® Classic
<b>Solution Tank</b>	4 gal (15 L)	8 gal (30 L)	11 gal (41 L)	7 gal (26 L)
<b>Recovery Tank</b>	4 gal (15 L)	6 gal (22 L)	8 gal (30 L)	7 gal (26 L)
<b>Brush Length</b>	12 in (30 cm)	15 in (38 cm)	18 in (46 cm)	14 in (35 cm)
<b>Vacuum Shoe</b>	14 in (35.5 cm)	18 in (46 cm)	20 in (51 cm)	17 in (43 cm)
<b>Coverage per Tank</b>	430 ft <sup>2</sup> (40 m <sup>2</sup> )	925 ft <sup>2</sup> (86 m <sup>2</sup> )	1530 ft <sup>2</sup> (142 m <sup>2</sup> )	755 ft <sup>2</sup> (70 m <sup>2</sup> )
<b>Vacuum Motor</b>	1.5 hp	1.5 hp	1.5 hp	1.5 hp
<b>Vacuum Motor Stages</b>	3 stage	3 stage	3 stage	3 stage
<b>Waterlift</b>	117 in (297 cm)	117 in (297 cm)	117 in (297 cm)	117 in (297 cm)
<b>Airflow</b>	95 cfm (2,690 L/min)	95 cfm (2,690 L/min)	95 cfm (2,690 L/min)	95 cfm (2,690 L/min)
<b>Spray Jets</b>	1	1	1	1
<b>Solution Flow Rate</b>	.7 gpm (2.65 L/min)	.7 gpm (2.65 L/min)	.7 gpm (2.65 L/min)	.7 gpm (2.65 L/min)
<b>Pump Pressure</b>	60 psi (4 bar)	60 psi (4 bar)	60 psi (4 bar)	60 psi (4 bar)
<b>Brush Motor</b>	.25 hp	.25 hp	.25 hp	.25 hp
<b>Power Cable</b>	40 ft (12 m)	40 ft (12 m)	40 ft (12 m)	40 ft (12 m)
<b>Height</b>	42 in (114 cm)	42 in (114 cm)	42 in (114 cm)	42 in (114 cm)
<b>Length</b>	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)	30 in (76 cm)
<b>Width</b>	15 in (38 cm)	19 in (48 cm)	21 in (53 cm)	18 in (46 cm)
<b>Weight</b>	99 lb (45 kg)	105 lb (47.7 kg)	111 lb (50.5 kg)	85 lb (38 kg)

MODELS:	Aquamatic Selectric™	AquaMax™	AquaRide® SE
<b>Solution Tank</b>	25 gal (95 L)	40 gal (151 L)	45 gal (170 L)
<b>Recovery Tank</b>	15 gal (56 L)	33 gal (145 L)	25 gal (95 L)
<b>Brush Length</b>	18 in (46 cm)	25 in (63.5 cm)	28 in (71 cm)
<b>Vacuum Shoe(s)</b>	20 in (51 cm)	2 - 15.5 in (39 cm)	2 - 15.5 in (39 cm)
<b>Productivity Per Hour</b>	5400 ft <sup>2</sup> (502 m <sup>2</sup> )		
<b>Productivity Per Hour - Maintenance Mode</b>		13,200 ft <sup>2</sup> (1,226 m <sup>2</sup> )	18,500 ft <sup>2</sup> (1,719 m <sup>2</sup> )
<b>Productivity Per Hour - Restoration Mode</b>		7,200 ft <sup>2</sup> (669 m <sup>2</sup> )	8,000 ft <sup>2</sup> (743 m <sup>2</sup> )
<b>Coverage per Tank for Maintenance Mode</b>	2800 ft <sup>2</sup> (2620 m <sup>2</sup> )		
<b>Restoration Mode</b>		26,750 ft <sup>2</sup> (2,485 m <sup>2</sup> ) 5,200 ft <sup>2</sup> (483 m <sup>2</sup> )	27,750 ft <sup>2</sup> (2,578 m <sup>2</sup> ) 5,500 ft <sup>2</sup> (511 m <sup>2</sup> )
<b>Vacuum Motor(s)</b>	1.5 hp	2 - 1.0 hp	2 - 1.0 hp
<b>Vacuum Motor Stages</b>	3 stage	3 stage	3 stage
<b>Waterlift</b>	117 in (297 cm)	72 in (183 cm)	72 in (183 cm)
<b>Airflow</b>	99 cfm (2,803 L/min)	93 cfm (2,633 L/min)	93 cfm (2,633 L/min)
<b>Spray jets</b>	1	2 - 1 per mode	2 - 1 per mode
<b>Solution Flow Rate for Maintenance Mode</b>	.8 gpm (3 L/min)		
<b>Restoration Mode</b>		.3 gpm (1.1 L/min) .9 gpm (3.4 L/min)	.5 gpm (1.9 L/min) 1.1 gpm (4.1 L/min)
<b>Pump Pressure</b>	60 psi (4 bar)	100 psi (6.9 bar)	100 psi (6.9 bar)
<b>Brush Motor(s)</b>	.33 hp	.5 hp	2 - .75 hp
<b>Drive Motor</b>	.1 hp	.5 hp	.8 hp
<b>Power Source</b>	75 ft cord (22.5 m)	(6) 6 V batteries	(6) 6 V batteries



# 800.440.6723

[www.southeasternequipment.net](http://www.southeasternequipment.net)



# Advance

by Nilfisk-Advance

14800 21st Avenue North  
Plymouth, MN 55447-3408  
[www.nilfisk-advance.com](http://www.nilfisk-advance.com)  
Phone: 800-214-7700  
Fax: 800-989-6566

396 Watline Avenue  
Mississauga, Ontario, Canada L4Z 1X2  
[www.nilfisk-advance.com](http://www.nilfisk-advance.com)  
Phone: 800-668-8400 or 905-712-3260  
Fax: 800-263-5111 or 905-712-3255