

NSS[®] Enterprises, Inc.

3115 Frenchmens Road Toledo, Ohio 43607-2958 USA www.nss.com





Wide-Area Vacuum



The Pacer 30 is the smart choice for fast, effective vacuuming of large carpeted areas. Its dual 1-HP vacuum motors provide impressive cleaning muscle in a single 30-inch (76.2 cm) pass.

- A unique vacuum muffling system, combined with extraordinary filtration make the Pacer 30 an exceptionally quiet wide-area vacuum.
- The large rear wheels and front swivel casters mean easy maneuverability.
- The Pacer 30's compact profile, adjustable handle, and self-propelling brush action make it easier and less tiring to use, compared to competitive vacuums.
- At a steady work pace, the Pacer 30 will cover 10,000 square feet (930 m²) of carpet per hour.
- The Pacer 30 is ideal for reception halls, meeting rooms, hotel hallways, airport terminals, or any other large areas that demand high-performance cleaning in a hurry.
- For above-the-floor cleaning tasks, the Pacer 30 can be ordered with a built-in tool kit. The tool kit features an on-board hose that stretches to 9.5 feet (2.9 m), a 2-piece wand, a crevice tool and a round brush.

Pacer 30 Specifications

Cleaning Path	30 in. (76.2 cm)	Filtration	4-stage clean air system,	Cord	75 ft. (22.9 m) 14-
Vacuum Motors -Quantity -Type -Voltage	2 Single-stage 115V. (230V. available)	-Capacity -Filter Area -Location -Type	3 internal and 1 exhaust filter (HEPA optional) 1.5 bu. (42.5 l.) 795 in. ² (5128 cm ²) Enclosed Cloth w/ zipper closure, w/ disposable paper filter bag	Overload Protection	3 SJT 17.5 amp reset circuit breaker
-HP -CFM -Closed Waterlift	1 HP (2 HP total) 194 ft.³ (5.5 m³) 44 in. (112 cm)			Sound Level	69 dbA @ operator
Brush Motor -Voltage -HP	115V. (230V. available) 1/3 HP	Switches & Controls Construction	Dual deadman levers	Dimensions -Length -Width	43.5 in. (110.5 cm) 31.75 in. (80.6 cm) 36 in. (91.4 cm)
-Bristles -Drive -Adjustment	Plastic cylinder core Nylon (adjustable wear) Poly v-belt, steel pulleys pile-height positions	-Body -Handle -Shoe -Wheels	Polyethylene Plated steel tubing w/ plastic grips Stainless steel (2) 10 in. (25.4 cm) rubber		100 lbs. (45.4 kg) 120 lbs. (54.5 kg)
-Speed -Width	1725 RPM 30 in. (76.2 cm)	-Casters	(2) 2 in. (5 cm) swivel type	Warranty	3 years limited 10 years poly parts
Productivity — Flo Cleaning Times.)	or coverage for the Pacer 30 is 10	0,000 sq. ft. per h	nour (930 m ²). (Floor coverage	e figures taken	from ISSA 447
<u>erearmig</u> rimeer,			Dual deadman lever	~ <u>~</u>	
	Padded handle provides increased operator comfort and machine control.				
	Ergonomic four- position handle adjusts to operator's height.			7	
		X		-Handle folds	
	polyethylene body ht or corrode.	~		convenient s	lorage.
			Compact profile reduces the distance dirt travels from vacuum intake to the filter bag for more efficient air movement.		
Optional HEPA ilters are available		-		Toe pedal ma adjustment to pile heights e five positions from.	o different easy —
	Double-row nylon brus rotates at 1725 RPM f self-propelled action a	or	("Quietbox" muffles and filters exhaust clean operation.)
Available with a built-in hose and co board tools for convenient above- he-floor cleaning.	deep cleaning.				
(nss,	NSS [®] Enterprises, Inc. 3115 Frenchmens Road Toledo, Ohio 43607-2958 US, 800/677-1663 or 419/531-2121 Fax 419/531-3761		RIBUTED BY		

Printed in USA

Fax 419/531-3761 *WWW.NSS.COM*

mailus @nss.com Specifications and appearance subject to change without notice.