WALK-BEHIND **AUTOMATIC SCRUBBERS**



DEFINING CLEANING INNOVATION



Advance Micromatic[™] 14E Walk-Behind Automatic Scrubber

- 14 inch scrub path, cord-electric
- Cylindrical scrub brush operates at 1,000 rpm
- Front and rear squeegee system picks up solution in all directions
- 3 gallon "lift-out" solution and recovery tanks



Advance Micromax[™] 17E/17B/20B Walk-Behind Automatic Scrubber

- Available in 17 or 20 inch scrub path cord-electric or battery
- 9.6 gallon solution and recovery tanks
- Standard onboard battery charger on battery models
- Click-off/Click-on scrub heads

BA 5321/D & BA 6124D

Walk-Behind Automatic Scrubbers

• 14.5 gallon solution and recovery tanks

Standard onboard battery charger

• Tip-back tanks for full accessibility

Click-off/Click-on scrub heads

• Available in 21 inch or 24 inch scrub paths

• Heavy-duty steel frame

Advance

Battery operated



COMMERCIAL EQUIPMENT

Advance ConvertaMAX[®] 20 & 26

Walk-Behind Automatic Scrubbers

- Available in 20 inch or 26 inch scrub paths
- 20 gallon solution and recovery tanks
- Click-off/Click-on scrub heads
- 2 brush pressure settings (70/110 lb)



Advance **CMAX® 28ST & 34ST**

Walk-Behind Automatic Scrubbers

- Available in 28 or 34 inch scrub paths
- 24 gallon solution and recovery tanks (28ST); 30 gallon (34ST)
- Equipped with Smart Solutions[™] for • enhanced safety and productivity.
- One-Touch[™] scrubbing and programmable operator controls.

Advance I-MAX[™] 28C & 32C

Walk-Behind Automatic Scrubbers

- Available in 28 or 32 inch scrub paths
- 30 gallon solution and recovery tanks
- Cylindrical scrub brushes with pre-sweep hopper
- One-Touch[™] scrubbing and programmable operator controls





Advance Convertamatic[®] 260B

Walk-Behind Automatic Scrubber

- 26 inch battery operated with Power-Flo[™] propulsion
- 18 gallon solution and recovery tanks
- Pad/brush pressure up to 215 pounds
- Legendary durability and cleaning power









WALK-BEHIND AUTOMATIC SCRUBBERS



DEFINING CLEANING INNOVATION

S P E C I F I C A T I O N S

MODELS:	Micromatic [™] 14E	Micromax [™] 17E	Micromax [™] 17B/20B	BA 5321	BA 5321/D & BA 6124D
Scrub Path(s)	14 in (36 cm)	17 in (43 cm)	17 in (43 cm) 20 in (51 cm)	21 in (53 cm)	21 in (53 cm) 24 in 61 cm)
Max Productivity - per hour @3 mph/4.8 kph	18,480 ft² (2,084 m²)	22,400 ft² (2,081 m²) 26,400 ft² (2,453 m²)	22,400 ft² (2,081 m²)/	26,400 ft ² (2,453 m ²)	26,400 ft ² (2,453 m ²)/ 31,680 ft ² (2,943 m ²)
·	(1) 14 in (20 and) and	(1) 17 : (12	(1) 17 := (42 ===)/	(1) 21 : (52) -li-	- (1) 21 in (E2 and) dia (
Scrub Head(s)	(1) 14 in (36 cm) cyl	(1) 17 in (43 cm) disc	(1) 17 in (43 cm)/	(1) 21 in (53 cm) dis	c (1) 21 in (53 cm) disc/
			20 in (51 cm) disc		(2) 12 in (31 cm) disc
Brush Motor	0.4 hp (300 W)	.74 hp (550 W)	.68 hp (510 W)	.75 hp (600 W)	.75 hp (560 W)/
					.88 hp (660 W)
Solution Tank	3 gal (11 L)	9.6 gal (36 L)	9.6 gal (36 L)	14.5 gal (55 L)	14.5 gal (55 L)
Recovery Tank	3.2 gal (12 L)	9.6 gal (36 L)	9.6 gal (36 L)	14.5 gal (55 L)	14.5 gal (55 L)
Vacuum Motor	1.2 hp (900 W)	.54 hp (400 W)	.68 hp (510 W)	.5 hp (380 W)	.5/.68 hp (380/510 W)
Sound Level	68 dB A	70 dB A	65 dB A	68 dB A	68 dB A
Drive System	Brush-Assist	Brush-Assist	Brush-Assist	Brush-Assist	.25 hp (200 W) fully variable forward and reverse
Length	25 in (62 cm)	47 in (119 cm) extended handle	47 in (119 cm) extended handle	52 in (132 cm)	52 in (132 cm)
Width w/o squeegee	16 in (40 cm)	20 in (51 cm)	20 in (51 cm)	21 in (53 cm)	21 in (53 cm) 24 in (61 cm)
Height	19 in (48 cm)	34 in (86 cm)-top of tank	34 in (86 cm)-top of tank	42 in (107 cm)	42 in (107 cm)
Squeegee Width	17 in (44 cm)	30.3 in (77cm)	30.3 in (77 cm)	30.3 in (77 cm)	30.3 in (77 cm) 32 in (81cm)
Weight	84 lb (38 kg)	276 lb (125 kg)	307 lb (139 kg) w/ std batteries	338 lb (153 kg) w/ std batteries	338 lb (153 kg) 346 lb (157 kg) w/ std batteries

MODELS:	Convertamatic [®] 260B	ConvertaMAX [®] 20/26	CMAX [™] 28ST	CMAX [®] 34ST	I-MAX [™] 28C/32C
Scrub Path (s)	26 in (66 cm)	20 in (51 cm)/ 26 in (66 cm)	28 in (71 cm)	34 in (86 cm)	28 in (71 cm)/ 32 in (81 cm)
Max Productivity - per hour (@ 3 mph/4.8 kph)	26,400 ft ² (2,453 m ²)	26,400 ft² (2,453 m²)/ 34,320 ft² (3,188 m²)	36,960 ft² (3,434 m²)	44,880 ft ² (4,169 m ²)	36,960 ft² (3,434 m²)/ 42,240 ft² (3,924 m²)
Scrub Head(s)	(2) 13 in (33 cm) disc	(1) 20 in (51 cm) disc /	(2) 14 in (36 cm) discs	(2) 17 in (43 cm) discs	(2) 27 in (53 cm)/
		(2) 13 in (33 cm) discs			31 in (79 cm) cyl brushes
Brush Motor	1.0 hp (746 W)	(1) 1.0 hp (746 W)/	(2) 0.75 hp (560 W)	(2) 0.75 hp (560 W)	(2) 1.0 hp (746 W)
		(2) 0.75 hp (560 W)			
Solution Tank	17 gal (64 L)	20 gal (76 L)	24 gal (91 L)	30 gal (114 L)	30 gal (114 L)
Recovery Tank	18 gal (68 L)	20 gal (76 L)	24 gal (91 L)	30 gal (114 L)	30 gal (114 L)
Vacuum Motor	.75 hp (560 W)	.75 hp (570 W)	.75 hp (570 W)	.75 hp (570 W)	.75 hp (570 W)
Sound Level	71 dB A	69 dB A	69 dB A	69 dB A	69 dB A
Drive System	Power-Flo forward- reverse	.5 hp (373 W) variable speed forward and reverse	.5 hp (373 W) variable speed forward and reverse	.5 hp (373 W) variable speed forward and reverse	.5 hp (373 W) variable speed forward and reverse
Length	53.5 in (136 cm)	59 in (149 cm)	64 in (163 cm)	64 in (163 cm)	65 in (165 cm)
Width (w/o squeegee)	27 in (67 cm)	20 in (51 cm)/27 in (69 cm)	29 in (74 cm)	35 in (89 cm)	29 in (74 cm) 33 in (84 cm)
Height	41 in (104 cm)	42 in (108 cm)	44 in (112 cm)	44 in (112 cm)	44 in (112 cm)
Squeegee Width	30.5 in (78 cm)	30 in (77 cm)/36 in (92 cm)) 36 in (92 cm)	45 in (114 cm)	36 in (92 cm)
Weight	702 lb (318 kg)	648 lb (294 kg)	759 lb (344 kg)	975 lb (442 kg)	1,015 lb (460 kg)



14600 21st Avenue North Plymouth, MN 55447-3408 www.nilfisk-advance.com Phone: 800-214-7700 Fax: 800-989-6566 ©2004, Nilfisk-Advance, Inc., 8/04, Form L1609A, Printed in U.S.A.

396 Watline Avenue Mississauga, Ontario, Canada L4Z 1X2 www.nilfisk-advance.com Phone: 800-668-8400 or 905-712-3260 Fax: 800-263-5111 or 905-712-3255