

Advance ConvertaMAX™/CMAX™ ST 28 & 34 Automatic Scrubbers



The ConvertaMAX™ 28 is shown above.

Some Ideal Applications Include:

- Hospitals & nursing homes
- Schools & universities
- Government facilities
- Supermarkets
- Shopping Malls
- Warehouses
- Retail stores
- Airports

The Advance ConvertaMAX™ and CMAX™ ST automatic scrubbers combine the best features of walk-behind scrubber technology in both 28 and 34 inch (71 and 86 cm) scrub path sizes.

Innovative features include a simple, ergonomic handle bar and control panel for all scrub functions.

Convenience features, include a rear port that permits filling the solution tank while dumping the recovery tank to save time. The easy-to-read solution level sight gauge tells how much solution is left in the tank. All these

Optional Accessories Include:

- Full range of brushes and pad holders for light to aggressive scrubbing
- Oil-resistant squeegee blades
- Scrub & Vac™ kit
- Metal- and oil-resistant cushioned casters,
- High tower roller bumpers

features help save time with set-up, clean-up and production time.

The scrub brushes float over uneven floors, and are gear-driven for optimum scrubbing speed and torque. Maneuvering is a breeze with the center drive wheel that can pivot on corners while the squeegee follows the scrub path for complete pick up.

Advance scrubbers have the durability and the quality you've come to expect. These scrubbers will be productive for a long time.



Advance ConvertaMAX™/CMAX™ ST 28 & 34 Automatic Scrubbers



Ergonomic handle design with integrated variable speed control gives optimal, comfortable control.



The recovery tank has a float system that shuts off vacuum air flow when the tank is full to prevent overflow.



Rear solution fill allows filling the solution tank while emptying the recovery tank for faster cycle times, more productivity.



Hinged recovery tank with safety latch gives easy maintenance access. Vac motor has sound deadening for quiet operation.

Integrated touch pad control panel includes: scrub on/off, vacuum on/off, max speed dial. Indicators include battery condition meter, hour meter.

Centered drive wheel provides traction and maneuverability. Machine pivots on drive wheel.

Rugged 24 gal. (91 l.) and 30 gal. (114 l.) polyethylene solution and recovery tanks are crack, dent and chemical resistant.

Solution sight gauge with indexed marks to monitor how much solution is left.

Scrub brushes have hands-free mounting and removal. (ConvertaMAX)

Rear solution tank fill port.

Swing-away squeegee disconnects to prevent damage.

Splash guard confines spray.

Squeegee automatically raises when scrubber backs-up. (ConvertaMAX)

38" (97 cm long, 2" (51 mm) dia-meter drain hose has soft, squeezable section for manual control of flow.

Simple "One Touch" Scrub Controls

Technical Specifications

	ConvertaMAX™ 28/CMAX™ 28 ST	ConvertaMAX™ 34/CMAX™ 34 ST
Cleaning Width	28" (71 cm)	34" (86 cm)
Cleaning Rate	37,100 sq. ft. (3447 m ²) per hour	44,388 sq. ft. (4124 m ²) per hour
Solution Tank	24 gal. (91 l.) capacity, roto-molded polyethylene, w/drain hose	30 gal. (114 l.) capacity, roto-molded polyethylene, w/drain hose
Recovery Tank	24 gal. (91 l.) capacity, roto-molded polyethylene, equipped with ball-float vacuum air shut-off.	30 gal. (114 l.) capacity, roto-molded polyethylene, equipped with ball-float vacuum air shut-off.
Scrub Brushes/Pads	Two 14" (35.5 cm) brushes or pad holders	Two 17" (43 cm) brushes or pad holders
Brush Speed	220 r.p.m.	220 r.p.m.
Brush Pressure	Variable to 600 lbs (272 kg) based on actuator rating	
Brush Drive Motor(s)	Two .75 hp, 560 watt motors	Two .75 hp, 560 watt motors
Vacuum Motor	.75 hp, 570 watt, three-stage	.75 hp, 570 watt, three-stage
Drive System ConvertaMAX™	.75 hp, 560 watt motor. Variable speed forward & reverse.	.75 hp, 560 watt motor. Variable speed forward & reverse.
Drive System CMAX™ ST	.50 hp, 373 watt motor. Variable speed forward & reverse.	.50 hp, 373 watt motor. Variable speed forward & reverse.
Weights	759 lbs. (344 kg) w/238 AH batteries 495 lbs. (225 kg) w/o batteries 600 lbs. (272 kg) shipping, (machine only) 864 lbs. (392 kg) shipping, (w/238 AH batt'ys)	975 lbs. (442 kg) w/238 AH batteries 579 lbs. (263 kg) w/o batteries 684 lbs. (310 kg) shipping, (machine only) 1080 lbs. (490 kg) shipping, (w/238 AH batt'ys)

Specifications are subject to change without notice.



Advance
by Nilfisk-Advance



Southeastern
EQUIPMENT & SUPPLY, INC.

800.440.6723

www.southeasternequipment.net