

# **Minuteman<sup>®</sup>**

*Excellence Meets Clean*



## **200X Series**

**Walk-Behind Automatic Floor Scrubbers**



**800.440.6723**

**[www.southeasternequipment.net](http://www.southeasternequipment.net)**



## General Overview

- Durable, highly maneuverable and user-friendly 20" automatic floor scrubber
- Wet scrubs and dry vacuums in one pass
- The series consists of Electric, Brush Drive, Traction Drive and Deluxe models
- Large solution/recovery tanks constructed of high impact polyethylene for longer scrubbing time & easy tank filling & flushing
- Solid epoxy coated steel frame thats built to last

## Productivity

- Wet scrubs and dry vacuums in one pass for maximum efficiency and productivity in high traffic areas
- 20" offset scrub head allows cleaning in tight areas and corners
- Available in brush drive traction drive to meet any cleaning needs
- Deluxe model has maxi-wall bladder system which increases tank size to maximize productivity

## Ease of Use

- Quick-release spring-loaded foot lever makes pad or brush replacement quick and easy
- Individual forward and reverse bail levers are convenient and easy to use
- User friendly control panel

## Key Features

- 20" cleaning path available in cord electric or battery
- Curved 4 sided breakaway, swing-type squeegee, no tools needed to change assembly or blades
- Offset scrub deck for excellent edge scrub capabilities
- Up front scrub head for easy brush change

## Safety

- Dead Man's switch
- Ergonomic operator handle
- Offset brush deck for better line of sight

## Markets


- Hospitality
- Institutional
- Industrial
- Healthcare
- Building Service Contractors
- Airports
- Retail

## Accessories/Options

- Multiple grit brushes to meet all cleaning needs
- Off-aisle wand
- Linatex squeegee blades

Specifications:	Electric	Brush Drive	Traction Drive	Deluxe
Scrub Path/Brush Diameter	20" (51 cm)	20" (51 cm)	20" (51 cm)	20" (51 cm)
Squeegee Width	35" (89 cm)	35" (89 cm)	35" (89 cm)	35" (89 cm)
Coverage Performance	21,500 sq.ft/hr (1,997 m <sup>2</sup> /hr)	21,500 sq.ft/hr (1,997 m <sup>2</sup> /hr)	21,500 sq.ft/hr (1,997 m <sup>2</sup> /hr)	21,500 sq.ft/hr (1,997 m <sup>2</sup> /hr)
Air Flow	90 cfm/min (2.55m <sup>3</sup> /min)	67 cfm/min (1.89m <sup>3</sup> /min)	67 cfm/min (1.89m <sup>3</sup> /min)	67 cfm/min (1.89m <sup>3</sup> /min)
Vacuum (Inches of waterlift)	90" (1,270 mm)	68" (1,727 mm)	68" (1,727 mm)	68" (1,727 mm)
Vacuum Motor	115v, 3-stage, 1 hp tangential bypass	24v, 3-stage, 1 hp tangential bypass	24v, 3-stage, 1 hp tangential bypass	24v, 3-stage, 1 hp tan gential bypass
Drive	Brush Propelled	Brush Propelled	Traction Drive	Traction Drive
Input Power	115 volt/ 230 volt CE	24 volt	24 volt	24 volt
Cord Length	75 feet (23 m)	-----	-----	-----
Batteries	-----	2- 12 volt 105 ah	2- 12 volt 210 ah	2- 12 volt 210 ah
Brush Motor	One 3/4 hp (.6 kw)	One 3/4 hp (.6 kw)	One 3/4 hp (.6 kw)	One 3/4 hp (.6 kw)
Brush Speed	250 rpm	200 rpm	200 rpm	200 rpm
Brush Pressure	Adj. up to 115 lbs. (52 kg)	Adj. up to 115 lbs. (52 kg)	Adj. up to 115 lbs. (52 kg)	Adj. up to 140 lbs. (64 kg)
Working Speed	0-215 ft/min (66 m/min)	0-215 ft/min (66 m/min)	0-215 ft/min (66 m/min)	0-215 ft/min (66 m/min)
Tank Capacities (Solution/Recovery)	14 gal (53 ltr)	14 gal (53 ltr)	14 gal (53 ltr)	Maxi-Wall Bladder System 20 gal (75 ltr)
Dimensions (LxWxH) (without squeegee)	57" x 24" x 40" (145 cm x 6 cm x 102 cm)	57" x 24" x 40" (145 cm x 6 cm x 102 cm)	57" x 24" x 40" (145 cm x 6 cm x 102 cm)	57" x 24" x 40" (145 cm x 6 cm x 102 cm)
Weight (without batteries)	246 lbs. (112 kg)	246 lbs. (112 kg)	246 lbs. (112 kg)	267 lbs (121 kg)
Weight (with batteries)	-----	517 lbs (235 kg)	517 lbs. (235 kg)	538 lbs (244 kg)
Wheel Diameter: Front	(2) 9" (23 cm) Solid	(2) 9" (23 cm) Solid	(2) 9" (23 cm) Pneumatic	(2) 8" (20 cm) Pneumatic
Caster Diameter: Rear	(2) 3 1/2" (23 cm)	(2) 3 1/2" (23 cm)	(2) 3 1/2" (23 cm)	(2) 3 1/2" (23 cm)
Brush Lifting Mechanism	Quick Release Foot Lever	Quick Release Foot Lever	Quick Release Foot Lever	Linear Actuator
Pump w/Brush Squeegee Tool	Optional	Optional	Optional	Standard

Specifications are subject to change without notice.



# 800.440.6723

[www.southeasternequipment.net](http://www.southeasternequipment.net)