



CREATING A CLEANER, SAFER, HEALTHIER WORLD.



# T3+

## COMPACT WALK-BEHIND FLOOR SCRUBBER

- Equipped standard with either ec-H2O™ or FaST® technology extends scrubbing up to three times longer between empty/fills
- Wider cleaning path and advanced technologies improve productivity
- Able to clean in the same spaces as a traditional 20 in / 500 mm scrubber
- Perfectly sized for small-sized and mid-sized retail facilities and route cleaners



**800.440.6723**  
[www.southeasternequipment.net](http://www.southeasternequipment.net)



## T3+ WALK-BEHIND FLOOR SCRUBBER

### SCRUBBING SYSTEM

Cleaning path	24 in / 600 mm
Productivity (per hour)	
Theoretical Max	28,560 ft <sup>2</sup> / 2,650 m <sup>2</sup>
Estimated Coverage*	18,150 ft <sup>2</sup> / 1,690 m <sup>2</sup>

### DRIVE SYSTEM

Brush motor horsepower	0.875 hp / 0.65 kW
Brush RPM	285 rpm
Brush/pad pressure	50, 90 lbs / 23, 41 kg

### SOLUTION DELIVERY SYSTEM

Solution tank description	Full access & cleanable
Solution capacity	10.5 gal / 40 L

### RECOVERY SYSTEM

Recovery tank description	Full access & cleanable
Recovery tank capacity (includes demisting chamber)	15 gal / 57 L
Vacuum motor	0.5 hp – two stage / 0.37 kW – two stage
Vac motor cfm	65 cfm / 1.84 cmm
Vac motor sealed waterlift	40 in / 1,020 mm

### BATTERY SYSTEM

Battery run time (continuous cleaning rating)	24V, 155 AH / Up to 3 hours
---	-----------------------------

### MACHINE SPECIFICATIONS

Product length	48.25 in / 1,225 mm
Product width (with squeegee)	30 in / 760 mm
Product height	43 in / 1,090 mm
Product weight (with batteries)	391 lbs / 177 kg
Sound level (operator's ear)**	68.5 dBA

### WARRANTY

See your local representative for warranty information

\*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers and OSHA.

Specifications subject to change without notice.

