



MODEL 1550 SELF-PROPELLED CARPET EXTRACTOR SPECIFICATIONS

Vacuum System

Cleaning path	24 in	610 mm
Vacuum motor (dual motors)	.9 hp(2)	17 A
Vacuum motor stages	3-stage	3-stage
Waterlift	135 in	3429 mm
Airflow	152 cfm	4.3 cmm
Recovery tank capacity	18 gal	67 L
Productivity (per hour)	6,000 ft ²	557 m ²

Solution & Brush System

Solution tank capacity	32 gal	121 L
Solution flow	1.2 gal / min	4.5 L / min
Spray jets	6	6
Pump pressure	100 psi	7 bar
Coverage rate per tank	2700 ft ²	250 m ²
Brush rpm	1200 rpm	1200 rpm
Brush motor	.5 hp	.5 hp

Total Power Consumption

Batteries / Cord	3 (12 V)	3 (12 V)
Amps	50 A	50 A
Voltage	36 V	36 V

Body Construction

Chassis	Polyethylene	polyethylene
---------	--------------	--------------

Optional Accessories

- Hand tool
- Solution hose extension
- Floor tools
- Upholstery tool
- Vacuum hose
- Floor wand

Tennant Company
Commercial Products
12875 Ransom Street
Holland, MI 49424
Tel: 616-786-2330; Fax: 616-786-2345
www.tennantco.com e-mail: tcoinfo@tennantco.com

(Specifications subject to change)
Some options may not be available in all countries.
6/01



800.440.6723

www.southeasternequipment.net