




**Commercial Floor Care Equipment**

## 3540 Battery Wet/Dry Vacuum



| Features  | Specifications   |
|---|--|
| <b>Product Name</b><br><b>Model Number</b>  | <b>3540</b><br><b>607623</b>   |
| <b>Chassis/Body Construction</b><br>Chassis Construction:<br>Caster Diameter:<br>Wheel Diameter:  | Rotationally-molded polyethylene<br>4 in / 0.16 cm<br>12 in /30.48 cm  |
| <b>Dimensions</b><br>Product Height:<br>Product Length:<br>Product Weight (without batteries):<br>Product Width:  | 43 in / 109.22 cm<br>33 in / 83.82 cm<br>90 lb/ 40.82 kg<br>21 in/ 53 .34 cm   |
| <b>Dirt/Debris Recovery System</b><br>Filter Description:   | Includes one cloth & one paper bag   |
| <b>Productivity</b><br>Maximum Coverage Rate Per Hour:<br>Run Time on full charge   | 20,000 ft <sup>2</sup> /h / 1858 m <sup>2</sup> /h<br>4 hours  |
| <b>Recovery System</b><br>Recovery Tank Wet Capacity:<br>Vacuum Hose Length:  | 16 gal/ 60.75 L<br>10 ft /3.05 m   |
| <b>Vacuum System</b><br>Airflow at Orifice:<br>Vacuum Motor Amps:<br>Vacuum Motor Diameter:<br>Vacuum Motor Horsepower:<br>Vacuum Motor Stages:<br>Vacuum Motor Type:<br>Vacuum Motor Voltage:<br>Vacuum Motor Watts:<br>Waterlift at Sealed Orifice: | 70 cfm /1.98 m3/h<br>23 A<br>5.7 in / 14.48 cm<br>.75 hp<br>3 stage<br>Acustek bypass<br>24 V<br>566 watts<br>70 in /177.8 cm  |
| <b>Optional Accessory Tools</b><br>Wet/Dry Kit (optional):<br><br>Other Optional Accessories:   | 16 inch /0.64 cm floor tool with adjustable brush, two-bend aluminum wands, 4 inch /10.16 cm upholstery tool, 11 inch /27.94 cm plastic crevice tool, 3 inch /7.62 cm round dusting brush, 14 inch/35.56 cm forward/reverse squeegee<br>Typhoon 39 inch /99.06 cm, 33 inch /83.82 cm and 26 inch /66.04 cm front mount squeegee kits, wet recovery bag, 16 inch /40.64 cm wet pick-up kit, contractor tool kit and 11inch /27.94 cm dry tool kit, two 105 A 12-volt or two 130 A12-volt batteries, 15 A battery charger. |