



# BR 2250/BR 2500 specifications



<b>Burnishing Models</b>	BR2250	BR2500
Pad diameter	20 in / 508 mm	
Pad motor	3.0 hp/ 2.20 kW	
Pad motor speed	2500 rpm	
Pad motor voltage	36 volts DC motor	
Pad pressure description	Variable: 15-45 lb / 7-20 kg	
Maximum coverage rate	27,500 ft <sup>2</sup> /h / 2,555 m <sup>2</sup> /h	
Burnish width	20 in / 508 mm	
<b>Battery System</b>		
Battery amp hour rating	240 A	305 A
Battery	(6) 6 V, 235 AH capacity batteries	
Battery description	Lead acid, deep cycle	
Battery run time per charge	Up to 3.5 hr	Up to 3.0 hr
<b>Productivity</b>		
Maximum coverage rate	27,500 ft <sup>2</sup> /h / 2,555 m <sup>2</sup> /h	
Cleaning width	20 in / 508 mm	
<b>Transport Drive System</b>		
Drive motor description	N / A	0.15 hp
Speed control system	N / A	Twist grips
Speed	N / A	150 ft / min & 270 ft / min
<b>Dimensions / Weight / Sound level</b>		
Length	53.125 in / 1350 mm	
Width	21.650 in / 550 mm	
Height	40.15 in / 1020 mm	
Net weight	230 lb / 107 kg	260 lb / 121 kg
Sound Level	75 dBa	
<b>Warranty</b>	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene parts.	

