barracuita

PRODUCT DATA



FEATURES:

- Available in 30", 34" & 38" models
- 30"/431 cc OHV V-VALVE Kawasaki engine 34" & 38"/585 cc OHV V-VALVE Kawasaki engine
- 2 year engine warranty (4 year option using Kawasaki approved oil)
- Partially enclosed body style enhances public-friendly appearance
- Low profile deck (under 4"/10 cm) for edge to edge operation
- RokBak[™] deck for easy brush/pad installation from standing position
- Counter-rotating brushes reduce strip splash
- Bail throttle with electronic clutch ensures smooth start-up by automatically engaging clutch at low speed during throttle-up and stops brush/pad rotation upon release
- Incrementally adjustable non-marking wheels for safe, smooth operation while allowing operator to control brush/pad pressure
- User-friendly advanced LED instrument panel and ergonomic padded handle
- KWA models feature SafeSense[®] Emissions Monitoring System; two minute warning light signals automatic shutdown
- Safe-Fill[™] cylinder prevents over filling; new and improved quick release strap makes cylinder removal and installation a snap
- Catalytic front mount muffler minimizes harmful emissions
- UL and CGA listed, CARB/EPA certified, CE approved*







©2005 AMANO PIONEER ECLIPSE® CORP. • 1 ECLIPSE ROAD • PO BOX 909 • SPARTA, NC 28675 USA 1-800-367-3550 • 1-336-372-8080 • FAX: 1-336-372-2895 • www.pioneer-eclipse.com

New & Reconditioned Equipment & Parts - www.southeasternequipment.net BARRACUDA LOW PROFILE PROPANE STRIPPING MACHINE

MODELS: BA30KWA/KWC* (76,2 cm)

ENGINE: Kawasaki (431 cc) OHV v-valve air-cooled

PERFORMANCE: 26,500 sq ft per hour (± 2400 m²) est.

ENGINE SPEED: 3600 rpm

BRUSH SIZE: (2) 16" (40,6 cm) brushes

BRUSH SPEED: 325 rpm

START: 12 v battery

WIDTH: 32" (81,3 cm)

LENGTH: 62" (158 cm)

HEIGHT: 42" (106,7 cm)

WEIGHT: 280 lb (127 kg)

SOUND LEVEL: 89 dB(A)

VIBRATION: Less than 2.5 m/s²

DECK: Sheet metal construction with hammertone powder coat finish

HANDLE: Welded steel adjustable **MODELS:** BA34KWA/KWC* (86,4 cm)

ENGINE: Kawasaki (585 cc) OHV v-valve air-cooled

PERFORMANCE: 30,000 sq ft per hour $(\pm 2700 \text{ m}^2)$ est.

ENGINE SPEED: 3600 rpm

BRUSH SIZE: (2) 18" (45,7 cm) brushes

BRUSH SPEED: 325 rpm

START: 12 v battery

WIDTH: 36" (91,3 cm)

LENGTH: 63" (160 cm)

HEIGHT: 42" (106,7 cm)

WEIGHT: 335 lb (152 kg)

SOUND LEVEL: 89 dB(A)

VIBRATION: Less than 2.5 m/s²

DECK: Sheet metal construction with hammertone powder coat finish

HANDLE: Welded steel adjustable **MODELS:** BA38KWA/KWC* (96,5 cm)

ENGINE: Kawasaki (585 cc) OHV v-valve air-cooled

PERFORMANCE: 33,500 sq ft per hour (± 3100 m²) est.

ENGINE SPEED: 3600 rpm

BRUSH SIZE: (2) 20" (50,8 cm) brushes

BRUSH SPEED: 325 rpm

START: 12 v battery

WIDTH: 40" (101,6 cm)

LENGTH: 64" (162,6 cm)

HEIGHT: 42" (106,7 cm)

WEIGHT: 355 lb (161 kg)

SOUND LEVEL: 89 dB(A)

VIBRATION: Less than 2.5 m/s²

DECK: Sheet metal construction with hammertone powder coat finish

HANDLE: Welded steel adjustable