



TM
Speed Scrub 2001 and 2001E

Automatic Scrubber

| Features | Specifications | |
|--|---|---|
| Model Name Model Number | Speed Scrub 2001 - Battery 608623/Canadian # 609243 | Speed Scrub 2001- Electric 08967 / Canadian # 609244 |
| Brush/Pad Drive System Brush Motor Amps: Brush Motor Hp: Brush Motor RPM: Brush Motor Vage: Brush Motor Watts: Brush RPM: Brush/Pad Design Description: Brush/Pad Pressure Maximum: | 20 amps .75 hp 220 rpm 24 V 550 watts 220 rpm Single, 20 in/50.8 m pad driver (standard) or 20 in/50.8 cm brush (optional) 50 lb /22.68kg | 6.5 amps .75 hp 250 rpm 120 V 550 watts 250 rpm Single, 20 in /50.8 cm pad driver (standard) or 20 in/50.8 cm brush (optional) 50 lb /22.68 kg |
| Battery System Battery Amp Hour Rating: Battery Count: Battery Run Time per Charge: Coverage Per Battery Charge: | 130 amp hour 2 2.5 hr 77,111 sq. ft. (7163.61 sq. m.) | N/A |
| Power Cord Power Cord Length: Power Cord Type: | N/A N/A | 75ft /22.8 m 14 gauge, 3-wire, SJTO yellow |
| Chassis/Body Construction | Rotationally-molded polyethylene | Rotationally-molded polyethylene |
| Dimensions Product Height: Product Length: Product Weight: Product Width: | 38 in/96.52 cm 47 in/119.38 cm 280 lb/127.01 kg(with batts.) 22 in/55.88 cm | 38 in/96.52 cm 47 in/119.38 cm 238 lb/ 107.95 kg 22 in /55.88 cm |
| Productivity Maximum Coverage Rate Per Hour: Cleaning Width: | 20,536 square ft (1907.79 square meters) 20 in/50.8 cm | |
| Recovery System Recovery Tank Wet Capacity: Squeegee Description: | 12 gal /45.42 L Forward/reverse pickup, free- floating, center-mounted, urethane blades, 27 in /68.5 cm | 12 gal/45.42 L Forward/reverse pickup, free- floating, center-mounted, urethane blades, 27 in /68.5 cm |
| Solution Delivery System | | |



800.440.6723

www.southeasternequipment.net

| | | |
|---|--|---|
| Coverage Rate Per Tank of Solution: Nominal Solution Flow Rate: Solution Capacity: | 5476 square ft (508.72 square meters) .5 gal (1.89l) per minute 10 gal /37.85 L | 5476 square ft (508.72 square meters) .5 gal (1.89l) per minute 10 gal /37.85 |
| Vacuum System Airflow at Orifice: Vacuum Motor Amps: Vacuum Motor Diameter: Vacuum Motor Hp: Vacuum Motor Stages: Vacuum Motor Voltage: Vacuum Motor Watts: Waterlift at Sealed Orifice: | 66 cubic ft (1.87 cubic meters) per minute 14 amps 5.7in /14.48 cm .5 hp 2 stage 24 V 350 watts 44 in /111.76 cm | 97 cubic ft (2.75 cubic meters) per minute 7.5 amps 5.7in /14.48 cm 1.15 hp 2 stage 120 V 866 watts 82 in /208.28 cm |
| Accessory Tools Accessories Included: | Package includes pad drivers, 2 batteries (130 amp hour, 12 V) and a battery charger. Red flashing safety lights. | Package includes pad drivers and red flashing safety lights. |
| Warranty | 10 years – Nobles warrants the rotationally-molded polyethylene housings and parts on all of its machines to be free from defects in materials and workmanship, under normal use and service for ten (10) years to the original end user. 3 years – Nobles guarantees the performance of non-polyethylene parts and components to be free from defects for up to three (3) years or 2,500 hours of operation. 3 years – Labor charges are covered for three (3) full years from the date of purchase for Nobles products, provided an authorized Nobles/Tennant service provider is used for repair. Travel is covered for (90 days). | |

| Features | Advantages/Benefits |
|--|--|
| Large wheels | Easy to maneuver |
| 10 gal solution and 12 gal recovery tank | Less down time |
| Forward/reverse pickup squeegee | Better pickup |
| Two, 130 amp hour, 12 V batteries (SS2001) | 3.75 hours of run time |
| 75ft power cord (SS2001E) | Large cleaning radius with less time spent searching for outlets |
| 50 lb of pressure | Better cleaning |
| Hinged recovery tank | Easy access for service and maintenance |
| 20in scrubbing path | Perfect for medium-size areas |
| Red flashing safety lights | Indicates machine is operating |
| Adjustable control panel | Comfortable for all operators |
| Automatic float shut-off | Shuts off vacuum motor when recovery tank is full; protects vacuum motor from damage |
| Fully automatic operation | Clean, uninterrupted for hours |
| Optional accessories | Select the right tool for any job |
| Rotationally-molded construction | Durable and long lasting |
| Nobles 10-3 Warranty | Buyer guarantee of quality |
| Made in the USA | Quality construction |



800.440.6723

www.southeasternequipment.net

