STALLION 8SC

8-Gallon Self-Contained Carpet Extractor



The Stallion 8SC features speed, maneuverability and deepdown cleaning, making it the perfect extractor for every carpet application. In fact, the Stallion 8SC is twice as fast as tub extractors, covering 1,400 square feet an hour.

The Stallion 8SC blasts solution through its three stainless steel jets into the carpet. The embedded dirt is agitated by the floating brush, which automatically adjusts to different carpet pile heights. The solution and loosened soil are then extracted by the powerful 1.88 HP vacuum motor. It cleans a 16-inch path in a single pass.

The Stallion 8SC has 8-gallon recovery and solution tanks; you have to empty and refill tanks less often, increasing productivity. The Stallion 8SC features a hinged, rotocast polyethylene body for easy maintenance of its internal components. The Stallion 8SC also has an accessory connector that allows it to be used with optional stair and upholstery cleaning tools.



NSS Enterprises, Inc. 3115 Frenchmens Road

nss,

3115 Frenchmens Road Toledo, Ohio 43607-2958 USA

The Stallion 8SC, because of its aggressive carpet cleaning ability, is ideal for offices, hotel rooms and areas where carpet restoration is required.

STALLION 8SC Specifications

TANK CAPACITY Solution Tank Recovery Tank	8 gal. (30 l.) 8 gal. (30 l.)	CONSTRUCTION Tanks Frame	Rotocast polyethylene Powder-coated steel	CORD Size	14-3 SJT safety yellow Twist-lock detachable plug
SOLUTION PUMP	100 PSI bypass Diaphragm type 115(110V.)-126.5(230V.)	SUCTION HEAD	16 in. (41 cm) corrosive- resistant cast aluminum	Length	50 ft. (15 m)
Watts				ACCESSORY VALVE	Quick-connect attach- ment; automatic valve
VACUUM MOTOR	3-stage tangential 110V120V. 220V240V. available	BRUSH	14.75 in. (37.5 cm) nylon bristle, ABS plastic core, "ν" design fill pattern	VALVL	actuated
Voltage				FLOAT SHUT-OFF	Ball type
HP Closed Waterlift	1.88 HP (1400 watts) 117 in. (297 cm)	BRUSH RPM	900 RPM, poly "V" belt	DIMENSIONS	
SPRAY JETS	3 stainless steel, ¼ turn snap in or out	BRUSH BEARINGS	Bearings sealed; additional seals with	Height Length Width	34 in. (86 cm) 35 in. (90 cm) 16 in. (41 cm)
CURRENT	120V. — 12 amps		string guard	vvidtri	
BRUSH MOTOR	240V. — 6.2 amps Permanent magnet 110V120V. 220V240V. available .125 HP 1200	WHEELS	Two 10 in. (25 cm) non- marking grey tread	WEIGHT	84 lbs. (38 kg)
Type Voltage				SHIPPING WEIGHT	100 lbs. (45 kg)
HP RPM		SOUND LEVEL	77 dbA @ operator	WARRANTY	3 year limited 10 year poly parts



Gaining access to the internal components of the Stallion 8SC is as easy as removing two bolts and lifting up on the body. Convenient fingertip controls make it easy to activate the Stallion's pump and vacuum motors.

The twist-lock connector prevents the cord from accidently being pulled out.

The accessory hook-up connector lets you use optional extraction tools with the Stallion 8SC.

> Three stainless-steel spray jets snap-in and snap-out for trouble-free maintenance.

A foam-sensitive ball-type float protects the vacuum motor from damage.

The 8-gallon polyethylene tanks won't dent, crack or corrode and are warranted for 10 years.


The vacuum shoe cleans a wide 16-inch path.



An optional 3-jet wand kit (4892869 — SOLD SEPARATELY) can be used with the Stallion 8SC to extract carpeted stairs and other hard-to-reach areas.



NSS® Enterprises, Inc. 3115 Frenchmens Road Toledo, Ohio 43607-2958 USA 419/531-2121 Fax 419/531-3761 www.nss.com mailus@nss.com Specifications and appearance subject to change without notice. The floating brush adjusts to different carpet pile heights. Stainless-steel string guards protect the brush bearings.



DISTRIBUTED BY

Printed in USA

©2002 NSS Enterprises, Inc.