

CREATING A CLEANER, SAFER, HEALTHIER WORLD.



6200

COMPACT RIDER SWEEPER

- Exceptional performance with efficient, one-pass sweeping and dust containment
- Superb maneuverability from compact size and easy operation
- Dramatically reduced cleaning costs with highly reliable
 Tennant parts and engineering



EXPERTLY-DESIGNED 6200 SWEEPER OFFERS EFFORTLESS OPERATION AND INCREASED PRODUCTIVITY



Engineered and built with Tennant's high quality parts, the 6200 delivers virtually continuous operation. Increase productivity with efficient one-pass cleaning, and multi-level dump hopper.

EXCELLENT SWEEPING AND DUST CONTROL

AutoAdjust™ design matches brush height to brush wear for sweeping of light dust and debris in one pass. The 6200's 2-stage dust control helps remove air-borne dust.

WORRY-FREE DURABILITY

Solid steel frame, hydraulic oil system and no-tool brush changes keep the reliable 6200 up and running.

EASY OPERATION FOR INCREASED PRODUCTIVITY

Excellent sightlines, easy-to-use controls, and the multi-level dump hopper makes for easy operation. The hopper can be emptied directly into containers up to 4.5 ft / 1.37 m.

800.440.6723 • www.southeasternequipment.net

INSIDE THE

6200



- Protect fixtures and equipment, as well as the sweeper, with the rear bumper and corner rollers.
- Maintain maximum cleaning power with the patented AutoAdjust™ brush cavity that automatically adjusts as bristles shorten.
- Thermo-Sentry™ monitors the hopper temperature and, in dangerously high temperatures, initiates vacuum shut-down.
- Effectively load different types of debris with adjustable four-sided, front-loading hopper and a sweeping system that can adjust to the type of debris.
- Conveniently empty hopper directly into containers up to 4.5 ft / 1.37 m.
- VCS° filter-shaking system effectively contains dust and keeps filter pleats free of clogs.



HIGH DUMP HOPPER FOR EASE OF USE AND OPERATOR SAFETY

The standard multi-level high dump hopper eliminates manual lifting, helping keep operator safe.

The large capacity hopper means more sweeping between dumpings.

MUST-HAVE OPTIONS

Extend cleaning reach

Access hard-to-reach areas with the optional instantly activated vacuum wand.

Enhance capability

QuickMop® effectively dry mops smooth concrete or finished surfaces with the mop's wide, 5.5 ft / 1.67 m, path.

Increase productivity

Dual side brushes expand the machine's sweeping reach to clean more floor space in less time.

800.440.6723 • www.southeasternequipment.net

TENNANTTRUE® PARTS, SERVICE AND FINANCE SOLUTIONS

- Reduce rework, labor and safety costs by using only Tennant True parts and service.
- Ensure optimal cleaning performance by selecting a Tennant True Service program provided by a network of over 400 factorytrained Tennant service representatives.
- Improve uptime by leveraging TennantTrue parts and service.
- Simplify budgeting by bundling Tennant*True* service plans, including parts, into the purchase or financing of your machine.
- Manage your cleaning program with real-time machine data from Tennant's IRIS™ technology.

Choose GE Capital or U.S. Bancorp, our leasing providers, for simple, quick financing with flexible upgrade options.

6200 COMPACT RIDER SWEEPER

SWEEPING SYSTEM

Cleaning path

One side brush 42 in / 1,070 mm
Two side brushes 55 in / 1,400 mm

Main brush

Main brush length (tubular)

Main brush drive

Main brush change

No-tool

Side brush diameter

28 in / 710 mm

Belt

No-tool

20.5 in / 520 mm

Debris hopper

 $\begin{array}{lll} \mbox{Volume capacity} & 4.4 \ \mbox{ft}^3 \ / \ 125 \ \mbox{L} \\ \mbox{Weight capacity} & 300 \ \mbox{lb} \ / \ 136 \ \mbox{kg} \\ \mbox{Dump height (variable to)} & 4.5 \ \mbox{ft} \ / \ 1.37 \ \mbox{m} \\ \end{array}$

DUST CONTROL SYSTEM

Filter system (dual stage, to 3 microns)

Stage 1 Perma-filter™ Stage 2 49 ft² panel filter / 4.6 m² panel filter

Dust filtration (to) 3 microns
Vacuum fan speed 4,300 rpm

PROPELLING SYSTEM

Battery package 235 Ah
Propelling motor 0.75 hp / 0.56 kW
Battery Model: Forward (variable to) 5.5 mph / 9 km/h
Reverse (variable to) 3 mph / 4.8 km/h
Gradeability

 Full hopper
 6.0 deg/11%

 Empty hopper
 10.0 deg/18%

MACHINE SPECIFICATIONS

77 in / 1,960 mm Length Width With one side brush 48.5 in / 1,230 mm With two side brushes 56 in / 1.420 mm Without side brush 42 in / 1,050 mm 56.5 in / 1,440 mm Height Weight With battery 2,034 lb / 923 kg Without battery 1,644 lb / 746 kg

WARRANTY

See your local representative for warranty information.

Specifications subject to change without notice.

