

Wet/Dry Vacuums



High-performance wet/dry vacuums to fit your cleaning needs.

Clean longer

Reduce the number of empty/fill cycles with either large capacity 15 gallon/57 liter or 16 gallon/60 liter tank.

Reduce maintenance costs

Prevent damage to the machine and your facility with a compact, rugged body made of durable polyethylene, backed by a 10-year warranty.

Multiple options

Choose a unit that's right for the application—whether it's the standard 15 gallon/57 liter unit, a pump out model, which pulls at a high rate and allows for easy emptying into taller sinks, or the battery operated model for greater flexibility and maneuverability. Optional tools and squeegees are available.



V-WD-15
(shown with optional squeegee)

Key Benefits

- Prevent vacuum damage with the float shut-off
- Gain easy access to the recovery tank and float shut-off with the flip-top lid
- Choose the wet/dry vacuum that's right for the application; a standard unit, battery operated or a pump-out model



800.440.6723

www.southeasternequipment.net



Wet/Dry Vacuums

V-WD-16B



Features	Specifications*		
Product Name	V-WD-15/V-WD-15S	V-WD-16P	V-WD-16B
Vacuum System Airflow at orifice Water lift at sealed orifice Motor amps Motor diameter Motor HP Motor stages Motor voltage Motor power	103 cfm / 2.9 m ³ /hr 92 in / 2336 mm 8.5 A 5.7 in / 144 mm 1.3 hp / .97 kW 2 stage 120 V 980 watts	112 cfm / 3.17 m ³ /hr 107 in / 2717 mm 10.7 A 5.7 in / 144 mm 1.6 hp / 1.2 kW 2 stage 120 V 1253 watts	70 cfm / 1.98 m ³ /hr 70 in / 1778 mm 23 A 5.7 in / 144 mm .75 hp / .56 kW 3 stage 24 V 566 watts
Debris Recovery System Filter description Recovery tank wet capacity Vacuum hose length	cloth bag / paper bag / intake filter 15 gal / 57 L 10 ft / 3 m	cloth bag / paper bag / intake filter 16 gal / 60.57 L 10 ft / 3 m	cloth bag / paper bag / intake filter 16 gal / 60.57 L 10 ft / 3 m
Chassis & Body Construction Chassis construction Caster diameter Wheel diameter	Rotationally-molded polyethylene 4 in / 102 mm 10 in / 255 mm	Rotationally-molded polyethylene 4 in / 102 mm 10 in / 255 mm	Rotationally-molded polyethylene 4 in / 102 mm 12 in / 305 mm
Power System Cord electric (cord length) Battery (run time per charge)	50 ft / 15 m —	50 ft / 15 m —	— 4 hours continuous
Standard Equipment Equipment	10 ft x 1.5 in / 3048 mm x 38.1 mm vacuum hose, one cloth and one paper filter bag, Contractor tool kit; dual bend aluminum wand with 14 in / 356 mm squeegee	10 ft x 1.5 in / 3048 mm x 38.1 mm vacuum hose and cloth filter bag	10 ft x 1.5 in / 3048 mm x 38.1 mm vacuum hose, one cloth and one paper filter bag, two batteries and battery charger
Optional Accessories Accessories	various sized front-mount squeegee kits, wet recovery bag, wet pick-up kit, contractor tool kit and dry tool kit	various sized front-mount squeegee kits, wet recovery bag, wet pick-up kit, contractor tool kit and dry tool kit	various sized front-mount squeegee kits, wet recovery bag, cloth filter bag, wet pick-up kit, contractor tool kit and dry tool kit
Standard Equipment Equipment (V-WD-15S only)	10 ft x 1.5 in / 3048 mm x 38.1 mm vacuum hose, one cloth and one paper filter bag and 26 in / 660 mm front mount squeegee	NA	NA
Optional Accessories Accessories (V-WD-15S only)	Contractor tool kit; dual bend aluminum wand with 14 in / 356 mm squeegee, wet pick up kit and dry tool kit	NA	NA
Dimensions Product Height Product Length Product Width Product Weight	37.5 in / 950 mm 29 in / 730 mm 15.5 in / 390 mm 44 lb / 20 kg	35 in / 890 mm 30 in / 762 mm 20 in / 510 mm 64 lb / 29.03 kg	43 in / 1092 mm 33 in / 840 mm 21 in / 533 mm 97 lb / 44 kg
Approvals	—	CSA, ETL	—
Warranty	See your sales representative or authorized distributor for complete warranty details.		

*specifications subject to change without notice



800.440.6723

www.southeasternequipment.net