Venom™, VN2015 & VN1715

20" & 17", 175 rpm, Low-Speed Buffers







800.440.6723

Simple. Rugged. Affordable.

Venom™, VN2015 & VN1715

20" & 17", 175 rpm, Low-Speed Buffers



STANDARD FEATURES:

SIMPLE

- Easy-to-use, fingertip controls
- Motor-mounted pad driver storage
- Universal clutch plate
- Safety lock-out switch

RUGGED

- 5-year housing warranty
- · 5-year warranty on motor
- All-steel, triple planetary gear box
- 1.5 hp, 66-frame motor
- · All-metal construction
- CSA approved
- Designed for heavy, daily use

AFFORDABLE

- Best value in the industry
- Pad driver included
- · High cleaning productivity rate
- Backed by the most extensive, hassle-free warranty in the business



SPECIFICATIONS	VN2015	VN1715
Deck Size	20 in (50.8 cm)	17 in (43.2 cm)
Pad Driver	19 in (48.3 cm)	16 in (40.6 cm)
Pad/Brush Speed	175 rpm	175 rpm
Voltage	110 V	110 V
Horsepower	1.5 hp (1.1 kW)	1.5 hp (1.1 kW)
Motor, Heavy-duty	66-frame	66-frame
Gear Box, All-steel	Triple planetary	Triple planetary
Sound Level	63 dBA	63 dBA
Power Cable, Safety Yellow	50 ft (15.2 m)	50 ft (15.2 m)
Wheels, Non-marking Grey	(2) 5 in (12.7 cm)	(2) 5 in (12.7 cm)
Amp Draw	13 amps	13 amps
Weight	109 lbs (49.4 kg)	101 lbs (45.8 kg)
Shipping Weight	123 lbs. (55.8 kg)	120 lbs. (54.4 kg)
Dimensions (L x W x H)	27 in x 20 in x 48 in (65.6 cm x 50.8 cm x 122 cm)	27 in x 17 in x 48 in (65.6 cm x 43.2 cm x 122 cm)
Optional Solution Tank	2.5 gal (9.46 ltr)	2.5 gal (9.46 ltr)
Optional Deck Sizes	15-in and 13-in decks 38 cm and 33 cm decks	15-in and 13-in decks 38 cm and 33 cm decks

and videos may be viewed online at www.usviper.com



Specifications are subject to change without notice.



