

Advance Whirlamatic™ VS20 and 20UHSB Battery-Powered Burnishers



Standard Features Include:

- Pad holder assembly

Some Ideal Applications Include:

- Hospitals/health care facilities
- Schools & universities
- Government buildings & installations
- Supermarkets
- Shopping malls
- Large retail stores
- Airports

Put a hard, high-gloss shine on large-area floors in a hurry with the Whirlamatic™ VS20 or 20UHSB battery-powered burnishers. These high-production models shine a 20 inch (51 cm) path at a rate of 27,000 square feet (2500 m²) per hour, saving time and money.

Side-by-side comparison tests using a gloss meter on a burnished floor show that the VS20 and 20UHSB produce a brighter shine than competitive battery burnishers.

One reason the VS20 and 20UHSB are so effective is the carefully balanced ratio of weight to pad speed, which produces a spectacular shine on a properly prepared floor. A fully floating pad holder follows uneven floor surfaces, for an

even shine. Results are an even, beautiful shine that resists scuffing and wear.

Both models feature a special dust-control system that collects dust in dual collector bags. No need for dust mopping the floor after each burnishing, it's left clean and shiny.

The VS20 model features variable-speed drive to the wheels, for easy transport and working maneuverability. Self-propelling drive on the VS20 glides over the floor with minimal operator effort. Both models have simple controls for easy operation.

Ask for a demonstration to see how these battery burnishers can save you time and money.



800.440.6723

www.southeasternequipment.net

Advance Whirlamatic™ VS20 and UHSB Battery-Powered Burnishers




Easy-to-use controls at the operator's fingertips. Gauges include battery condition indicator, load indicator and a brush wear indicator light



Twist grips start the pad for the VS20 and 20UHSB. Twist grips on the VS20 control the variable speed in forward and reverse. Variable speed goes from 0 to 270 feet per minute (0-82 meters/min.).



Sturdy battery tray protects components and floor below. It's impervious to battery acid and catches spills that might occur.



Effective dust control system picks up dust with dual collector filter bags while burnishing. Eliminates dust mopping... saves you time and money.

Low Sound Level – both models only 68 dBA at operator's position

Unbeatable shine with carefully balanced ratio of weight to pad speed.

Optional VS20 hour meter tells you when it's time for service.

25 percent more run time with optional six volt battery package.

Easy-to-use twist grip controls propel the VS20 at variable speeds in forward and reverse.

Dual clean air ducts protect the motor from dust and provide cooling for longer life.

Convenient foot pedal raises and lowers pad.

Dust-free performance with dual collector bags.

Machine tips back for easy access to pad and dust collector filter bags.

Heavy duty construction and non-marking roller bumpers protect walls and furniture as well as the machine.

Direct drive motor to pad for optimum performance and longer run time.

Tight areas are no problem... VS20 turns in its own length.

Variable speed wheel drive makes the VS20 easy to transport and maneuver.

Setting Standards...

- Our products are value-priced to give you the best combination of price and performance for your investment.
- You can get expert service and maintenance for your products by factory-trained personnel around the world, as well as fast parts delivery.
- Maintain peak performance with genuine **apa** parts.

Technical Specifications

	<i>Whirlamatic VS20</i>	<i>Whirlamatic 20UHSB</i>
Motors:	2.5 hp, 36V DC	2.5 hp, 36V DC
Propulsion Means:	Permanent magnet drive motor,	Manual push fully variable forward/reverse
Batteries:	(3) 185 amp hr/12V or (6) 238 amp hr/6V	(3) 185 amp hr/12V or (6) 238 amp hr/6V
Sound Level:	68 db(A) at operator position	68 db(A) at operator position
Pad Holder:	Permanently mounted, flexible, Floats vertically and front to rear	
Pad Pressure:	Fully adjustable	Fully adjustable
Pad Speed (r.p.m.):	Varies with pressure/amp draw (2,500 no load, 2,000 under load)	
Pad Size:	20" (51 cm) diameter	20" (51 cm) diameter
Dust Collection:	(2) paper filter/collector bags mounted on specially designed dust control shroud/pad housing, heavy-duty felt edging material seals/controls air flow	
Length:	46" (117 cm)	46" (117 cm)
Width:	25.5" (65 cm)	25.5" (65 cm)
Height:	40" (102 cm)	40" (102 cm)
Weight w/o Batteries:	227 lb. (103 kg)	171 lb. (78 kg)
Weight w/3 x 185 Amp Hr Batteries:	612 lb. (278 kg)	556 lb. (252 kg)
Weight w/6 x 238 Amp Hr Batteries:	652 lb. (296 kg)	596 lb. (270 kg)
Shipping Weight:		
(machine only)	302 lb. (137 kg)	246 lb. (112 kg)
Part Number:	56 393 705	56 393 500

Specifications are subject to change without notice.

*Burnishing rate based on straight burnishing time at maximum speed and does not take into account brush/pad overlap, obstacles or turn-about time. Individual rates may vary.



**Nilfisk
Advance**
setting standards

Southeastern
EQUIPMENT & SUPPLY, INC.

800.440.6723

www.southeasternequipment.net