

# All Surface Cleaner



**Keep restrooms and hard surfaces sparkling clean with the all surface cleaner.**

The All Surface Cleaner is the right solution for the number one cleaning challenge—restrooms. It's also a great match for cleaning other hard surfaces like stairwells, windows and more.

### **Multifunctional cleaner**

The All Surface Cleaner cleans and rinses fixtures and surfaces, blows dry the rinsed surfaces and then recovers dirty water without the operator touching a surface. After cleaning, the recovery tank easily empties using a drop-down drain hose or power pump-out system.

### **Tools and accessories**

This portable cleaner comes complete with ten standard tools and accessories, including a telescopic vacuum wand and a separate expandable clean-air blower hose.



## Key Benefits

- Replace your mop and bucket with the All Surface Cleaner, which is the preferred solution for cleaning restrooms and other hard surfaces
- Increase productivity and employee safety and morale with this touch-free method of cleaning
- Ideal for use on sinks, toilets, urinals, shower stalls and other non-porous surfaces in locker rooms, restrooms, stairwells and more



**800.440.6723**

[www.southeasternequipment.net](http://www.southeasternequipment.net)



# All Surface Cleaner



Features	Specifications*
<b>Product Name</b>	ASC-15
<b>Vacuum/Recovery System</b> Airflow at 2 in / 50 mm orifice Water lift at sealed orifice Vacuum motor type  Vacuum motor amps Vacuum motor stages Vacuum motor voltage Vacuum motor watts	99 cfm / 2.8 m <sup>3</sup> /hr 117 in / 2982 mm Single speed, tangential discharge, 5.7 in / 144 mm diameter, dual ball bearings epoxy painted fan case, recognized by UL 10 A 3 stage 120 V AC 1200 watts
<b>Solution/Recovery Tanks</b> Solution tank capacity Recovery tank capacity	15 gal / 56.7 L 19 gal / 71.9 L
<b>Blower System</b> Motor (1) Water lift at sealed orifice Vacuum motor type Vacuum motor amps Vacuum motor stages Vacuum motor voltage Vacuum motor watts	Separate blower motor 91 in / 2311 mm Single speed, UL, CSA 10 A 2 stage 120 V AC 1000 watts
<b>Power System</b> Power cord length Power cord type	25 ft / 7.6 m, GFCI (120 V, 15 A, Class A) 14 gauge, 3 wire, SJTO: recognized by UL and CSA, non-marking safety yellow
<b>Dimensions/Weight/Sound level</b> Height Width Length Net weight Sound level (operator's ear)	37.5 in / 953 mm 18.5 in / 470 mm 36.5 in / 927 mm 126 lb / 57 kg 82 dBA
<b>Standard Equipment</b>	Two-piece telescopic aluminum vacuum wand, 25 ft / 7.6 m, 1.5 in / 38 mm diameter recovery hose (black), 25 ft / 7.6 m expandable gray clean air blower hose, 25 ft / 7.6 m high pressure hose with quick-connect variable pressure gun, scrub brush, floor squeegee tool, hand squeegee tool, blower tool, gulper floor drain tool, chemical metering tip packet, fill hose
<b>Approvals</b>	CSA
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.

\*Specifications subject to change without notice



# 800.440.6723

[www.southeasternequipment.net](http://www.southeasternequipment.net)