



**Typhoon™ EV  
Wet/Dry Vacuum**

Features		Specifications	
<b>Model Name:</b>	<b>Typhoon™ EV 1592</b>	<b>Typhoon™ EV 1512</b>	
<b>Model Number:</b>	<b>608688/Canadian # 609533</b>	<b>608689/Canadian # 609534</b>	
<b>Chassis/Body Construction</b>	Rotationally-molded polyethylene		
Caster Diameter	4 in/ 10 cm		
Wheel Diameter	10 in/ 25 cm		
<b>Vacuum Recovery System</b>			
Airflow at Orifice	103 cfm/ 2.9 m <sup>3</sup> /hr	100 cfm/ 2.9 m <sup>3</sup> /hr	
Water lift at Sealed Orifice:	92 in/ 233 cm	120 in/ 233 cm	
Vacuum Motor Horsepower:	1.3 hp	1.6 hp	
Vacuum Motor Amps:	8.5 A	10.7 A	
Vacuum Motor Diameter:	5.7 in/ 14 cm	5.7 in/ 14 cm	
Vacuum Motor Stages:	2 Stage	3 Stage	
Vacuum Motor Voltage:	120 V	120 V	
Vacuum Motor Watts:	980 Watts	1242 Watts	
Recovery Tank Capacity:	15 gal/ 56 L	15 gal/ 56 L	
Vacuum Bag Capacity:	1/3 bushel/ L	1/3 bushel/ 10 L	
<b>Dimensions</b>			
Product Height:	37.5 in/ 95 cm		
Product Length:	29 in/ 73 cm		
Product Width:	15.5 in/ 39 cm		
Product Weight:	44 lb/ 20 kg		
<b>Power Cord</b>			
Power Cord Length	50 ft/ 15 m		
<b>Accessories/Tools Standard</b>	10 ft x 1.5 in/ 2 cm x 3 cm vacuum hose, standard drain hose. Contractor tool kit: Dual bend aluminum wand.		
<b>Optional Accessories</b>	The 26 in/ 66 cm, 33 in/ 83 cm, or 39 in/ 99 cm Squeegee Attachment Kit. 14-inch scalloped face carpet tool and bags sold separately.		

Nobles Industries • 12875 Ransom Street • Holland, MI 49424 • USA • (800) 522-7839 • Fax (616) 786-2345  
Specifications Subject to Change Without Notice.

Rev 9/99 bjb