

PATENT PENDING

20 GALLON BATTERY-POWERED DUAL SPRAYER

OPTI-MIST 20B

The Opti-Mist[™] 20B is the ultimate in spot spraying or wide-area spraying in large buildings where productivity is a must. The operator has the choice of using the hand sprayer or switching to the adjustable spray bar below to make quick work of floor spraying. This dual sprayer (patent pending) provides a consistent, controlled mist.

- The hand sprayer comes with a 25' coiled hose for efficient flexibility. The operator can spray inside a room without having to maneuver the machine through the door.
- The spray bar adjusts in width to spray mist on the floor in a path ranging from 22 to 84 inches.
- The Opti-Mist 20B's high capacity 20-gallon tank holds enough solution to spray up to 60,000 square feet per tank.
- The Opti-Mist 20B's battery pack allows up to ten hours of run time and lets your staff quickly apply chemicals to surfaces anywhere, without the hassle of cords.







If using the Opti-Mist 20B with a disinfectant, be sure to follow the chemical manufacturer's instructions regarding application, dilution, coverage and dwell time.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

OPTI-MIST 20B

••••••	
Floor Spray Path	Variable, 22" to 84 "
Tank Capacity	20 Gallons (76 L)
Coverage per Tank	Up to 60,000
Operating Pressure	60 PSI
Hose Length	25' coiled hose (7.6 m)
Hose Material	Polyurethane
Hand Spray Wand	Sprayer with 25 foot hose
Hand Spray Nozzle	Stainless Steel, 110° Fan
Hand Spray Rate	0.05 GPM
Floor Spray Nozzle	Stainless Steel, 110° Fan (Qty 6)
Floor Spray Rate	0.10 GPM Per Nozzle
Construction Tanks Base Housing Wheels Casters	Rotomolded polyethylene Welded steel Mounted on hinges Two 8-in (20 cm) roller bearing Two 6-in (15 cm) ball bearing swivel
Charger Voltage	120V or 240V
Battery Charger	On-Board
Batteries	2 x 12V, 35 AH AGM
Run Time	Up to 10 hours
Sound Level	65 dBA
Dimensions L x W x H	47 x 24 x 41 inches 119 x 60 x 104 cm
Weight Machine Shipping	156 lbs (71 kg) 195 lbs (88 kg)
Warranty	3 years parts, 1 year labor, 10 years on tanks.
Patent	on tanto.

(nss

NSS ENTERPRISES, INC.

3115 Frenchmens Road Toledo, OH 43607-2958 USA (800) 677-1663 TEL (419) 531-3761 FAX info@nss.com

NSS.COM



- 1. The built in spray wand and 25' hose lets your staff spray any surface they can reach.
- 2. Lock-on spray wand for fatigue free spraying.
- **3.** Two filters, a strainer on the tank and an in-line filter protect the spray tip from clogging.
- **4.** The durable 20 gallon tank won't rust or corrode and has a 10 year warranty.
- 5. An on-board charger allows the Opti-Mist 20B to be charged anytime, anywhere.
- 6. Each spray bar has a valve, allowing the operator to adjust or shut off the spray on each side of the machine.
- **7.** The spray bars fold in, making transport through doors and into elevators easy.

WARNING

It is a violation of Federal law to use a chemical in a manner inconsistent with its label. Read and follow the chemical's label and SDS. Use personal protective equipment as detailed by the chemical product's SDS. Excessive exposure to disinfectants and other types of chemicals might be harmful to one's health.