

# **WARHORSE 27**

## **27-Inch Propane Burnisher**



For the ultimate in high-gloss shine, the Warhorse 27 Propane Burnisher is the perfect machine. This rugged buffer is built with the safest engine and emission control system available today. In fact, the Warhorse 27 is designed with the most up-to-date technology in the industry.

Built with the rugged 20-HP Onan "Performer" engine on a 14-gauge steel frame, the Warhorse 27 is wide enough to buff 40,000 square feet per hour. A full tank of propane will last more than three and a half hours, keeping the Warhorse 27 on the job longer than most propane buffers.

The Warhorse 27 is also available with the Vac-Trac™ Dust Collection System, which eliminates the powdered residue caused by burnishing old floor finishes.

A Low Oil Pressure Switch and Emission Warning Light are just two of the safety features on this machine that allow it to meet EPA and California emission regulations.



**NSS Enterprises, Inc.**  
3115 Frenchmens Road  
Toledo, Ohio 43607-2958  
USA

ISO 9001  
CERTIFIED



FM 40553



# **800.440.6723**

**[www.southeasternequipment.net](http://www.southeasternequipment.net)**

# WARHORSE 27 Specifications

PAD SPEED	1600 RPM	CLUTCH	Centrifugal	DIMENSIONS	
PAD DRIVER	Flexible polypropylene	STARTER	12V. electric	Length	66 in. (168 cm)
PAD SIZE	27 in. (69 cm)	THROTTLE CONTROL	Deadman at operating handle	Width	29 in. (74 cm)
ENGINE Type	Onan "Performer" Twin cylinder	CONSTRUCTION	Reinforced 14-gauge steel, powder coated	Tank Height	34 in. (86 cm)
HP	Nominal 20 HP	DRIVE SYSTEM	Dual v-belts w/ dual bearings	Handle Height	43 in. (109 cm)
Size	48 in. <sup>3</sup> (786.6 cm <sup>3</sup> )	WHEELS	2 rubber 6 in. (15.2 cm) 2 dolly wheels 3 in. (8 cm)	WEIGHT	
FUEL SYSTEM	Propane 20 lb. tank LP vapor withdrawal	SOUND LEVEL	85 dbA	Machine w/ tank	270 lbs. (123 kg)
BATTERY	32 amp hour 12V. sealed gel	HANDLE	Adjustable height by wrench	Vac-Trac™/ tank	309 lbs. (140 kg)
				SHIPPING WEIGHT	
				Machine w/ tank	375 lbs. (170 kg)
				Vac-Trac™/ tank	414 lbs. (188 kg)
				WARRANTY	
				Fuel System	3 year limited 2 year Onan

The Vac-Trac™ Dust Collection System controls powdering which can occur when burnishing older style floor finish formulations. Powder is removed through the natural air movement caused by the rapidly spinning pad. The vacuum system captures the powder and collects it in a filter bag located at the rear of the machine. This feature aids IAQ, and eliminates the "snowy" residue often left behind by other burnishers.



## Transport Position

In the transport position, the Warhorse 27 rests on two 6-inch (15.2 cm) wheels and two 3-inch (7.6 cm) wheels.



## Pad Change Position

In the pad change position, the Warhorse 27 rests on the two smaller wheels and two rubber feet at the rear of the buffer.



## Emission Warning Light

An Emission Warning Light, which prevents harmful emissions, is built right into the 20-HP Onan "Performer" engine.



**NSS® Enterprises, Inc.**  
3115 Frenchmens Road  
Toledo, Ohio 43607-2958 USA  
419/531-2121 Fax 419/531-3761  
[www.nss.com](http://www.nss.com)  
[mailus@nss.com](mailto:mailus@nss.com)  
Specifications and appearance  
subject to change without notice.

## DISTRIBUTED BY



**800.440.6723**

[www.southeasternequipment.net](http://www.southeasternequipment.net)

Printed in USA

©2000 NSS Enterprises, Inc.

#9096506 REV A 9/00