www.southeasternequipment.net

Canister Extractors

EX-CAN-15LP / EX-CAN-15HPH



Portable low and adjustable pressure canister carpet extractors make quick work in tight areas.

Control your clean

Pick the model that meets your cleaning needs. Prevent over-wetting with an adjustable water pressure unit with built-in heater to increase cleaning power or choose the standard 100 psi model.

Simple maintenance, easy mobility

Get quick, easy access to working parts with the convenient clamshell design. The extractor's large rear wheels increase mobility and allow for easier transportation on stairs.

Low cost life-cycle

Strong and robust construction means years of dependable use. The unique bladder design maximizes solution/recovery while minimizing the unit's footprint.

Key Benefits

- Straightforward, simple design makes this unit easy to use and maneuver
- Patented bladder design keeps machine compact
- Choose from a low pressure (100 psi) unit or adjustable pressure (0-250 psi) with heat extractor

1075-67 02/10

©2010 Tennant and Nobles are registered trademarks of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.

Tennant
701 North Lilac Drive
Minneapolis, MN
55440-1452, USA

800.553.8033
763.540.1200
In Quebec: 514.335.6061

www.tennantco.com
info@tennantco.com



Canister Extractors

EX-CAN-15LP / EX-CAN-15HPH

Features	Specifications*	
Product Name	EX-CAN-15 LP (low pressure)	EX-CAN-15 HPH (high pressure w/ heat)
Solution System		
Solution pump pressure	100 psi / 6.9 bar	0-250 psi / 0-17.22 bar (variable)
Solution pump voltage	120 V	120 V
Solution pump amps	1 A	5 A
Solution pump open flow rate	1.8 gpm / 6.81 L/min	2.4 gpm / 9 L/min
Heat Exchanger		
Description	—	Cast aluminum, hairpin element cast into aluminum, surface mount thermostat; preset to 170°F (76.6°C) for safety
Vacuum System		
Airflow at 2 in / 50 mm orifice	101 ft^3 / 2.8 m^3/h	
Water lift at sealed orifice	137 in / 3480 mm (LP) / 134 in /3403 mm (HPH)	
Vacuum motor type	Single speed, tangential discharge, 5.7 in / 145 mm diameter, dual ball bearings, epoxy painted fan case; recognized by UL	
Vacuum motor power	1.66 hp / 1.23 kW (LP) / 2.5 hp / 1.87 kW (HPH)	
Vacuum motor stages	3 stage	
Vacuum motor voltage	120 V AC	
Vacuum motor amps	13 A (LP) / 10 A (HPH)	
Tank Capacity		
Solution tank capacity	15 gal / 56.7 L	
Recovery tank capacity	19 gal / 71.9 L	
Chassis/Body Construction		
Construction type	Rotationally-molded polyethylene	
Caster diameter (locking)	4 in / 100 mm	
Wheel diameter	12 in / 305 mm	
Power Cord		
Power cord length	25 ft / 7.6 m, 1 cord / 2 cord (EX-CAN-15 HPH)	
Power cord type	14 gauge 3 wire SJTO, recognized by UL and CSA, safety yellow, detachable	
Standard Tools/Accessories		
Tool/accessory description	Low pressure (EX-CAN-15 LP) / High pressure (EX-CAN-15 HPH) 13 in / 330 mm floor tool with three spray jets, stainless steel wand/shoe, 15 ft x 1.5 in / 4.5 m x 380 mm vacuum hose, 15 ft x 3/8 in 4.5 m x 90 mm solution hose Contact your sales representative or authorized distributor for information on additional accessories.	
Dimensions/Weight/Sound Level		
Length/Width/Height/Weight/Sound	L: 38 in / 965 mm, W: 19 in / 482 mm, H: 38 in / 965 mm, Wt: 110 lb / 49.8 kg (LP) 145 lb / 65.7 kg (HPH), 82 dBA	
Approvals	CSA	
Warranty	See your sales representative or authorized distributor for complete warranty details.	

*Specifications subject to change without notice

1075-67 02/10

©2010 Tennant and Nobles are registered trademarks of Tennant Company, whose products are sold and serviced through Tennant Sales and Service Company, as well as through distributors.

Tennant
701 North Lilac Drive
Minneapolis, MN
55440-1452, USA

800.553.8033
763.540.1200
In Quebec: 514.335.6061

www.tennantco.com
info@tennantco.com