

Click the model number below...

1240 (16 inch)

1260 (20 inch)



Model 1240 Specifications

CARPET EXTRACTOR

Feature	English / Metric
Brush Drive System	
Brush bristle type	Offset rows of nylon bristles in a chevron pattern
Brush diameter	3.31-inch/ 84 mm
Brush length	13-inch/ 330 mm
Brush motor amps	1.5 amp
Brush motor power	0.25 hp/ 0.18 kW
Brush RPM	1,380 rpm
Motor RPM	2,300 rpm
Chassis/Body Construction	
Chassis construction	Rotationally-molded polyethylene
Metal parts coating	Zinc plating w/ yellow chromate
Wheel descriptions	Non-marking gray tread
Recovery System	
Airflow at 2-inch (50 mm) orifice	95 ft ³ / min/ 345 m ³ /min
Vacuum motor power	1.8 hp/ 1.34 kW
Vacuum motor stages	3 stage
Vacuum motor amps	13 A max
Recovery capacity	14.5 gallon/ 55 liter
Sealed waterlift	136-inch/ 3454 mm
Machine Dimensions	
Length	43-inch/ 1092 mm
Machine Width	16-inch/ 406 mm
Height	34-inch/ 863 mm
Weight	104 lb/ 47.5 kg
Solution System	
Solution tank capacity	10 gallon/ 38 liter
Solution pump amps	1 amp
Solution pump pressure	100 psi/ 690 kPa
Pump flow rate	1 gpm/ 3.8 L/min
Solution valve	Electric solenoid
Spray jet count	Dual, quarter turn w/ large grip
Power Consumption	
Amps	14.5 amps
Voltage	120 VAC
Watts	1740 watts
Power Cord	
Power cord length	50 ft/ 15.24 m- detachable
Power cord type	16 gauge, safety yellow
Sound Level	
Decibel rating at operator's ear	78 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.



Model 1260 Specifications

CARPET EXTRACTOR

Feature	English / Metric
Brush Drive System	
Brush bristle type	Offset rows of nylon bristles in a chevron pattern
Brush diameter	3.31-inch/ 84 mm
Brush length	17-inch/ 431 mm
Brush motor amps	1.5 amp
Brush motor power	0.25 hp/ 0.18 kW
Brush RPM	1,380 rpm
Motor RPM	2,300 rpm
Chassis/Body Construction	
Chassis construction	Rotationally-molded polyethylene
Metal parts coating	Zinc plating w/ yellow chromate
Wheel descriptions	Non-marking gray tread
Recovery System	
Airflow at 2-inch (50 mm) orifice	95 ft ³ / min / 345 m ³ /min
Vacuum motor power	1.8 hp/ 1.34 kW
Vacuum motor stages	3 stage
Vacuum motor amps	13 A max
Recovery capacity	14.5 gallon/ 55 liter
Sealed waterlift	136-inch/ 3454 mm
Machine Dimensions	
Length	43-inch/ 1092 mm
Machine Width	20-inch/ 508 mm
Height	34-inch/ 863 mm
Weight	106 lb/ 48.2 kg
Solution System	
Solution tank capacity	10 gallon/ 38 liter
Solution pump amps	1 amp
Solution pump pressure	100 psi/ 690 kPa
Pump flow rate	1 gpm/ 3.8 L/min
Solution valve	Electric solenoid
Spray jet count	Dual, quarter turn w/ large grip
Power Consumption	
Amps	14.5 amps
Voltage	120 VAC
Watts	1740 watts
Power Cord	
Power cord length	50 ft/ 15.24 m- detachable
Power cord type	16 gauge, safety yellow
Sound Level	
Decibel rating at operator's ear	78 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.