



# Model 2320 Specifications

## HIGH SPEED BURNISHER

Feature	English / Metric
<b>Pad Drive System</b>	
Motor volts	120 V
Motor amps	15 amp
Motor power	1.5 hp/ 1.1 kW
Motor type	Permanent magnet DC, circuit breaker protected
Pad diameter	20-inch/ 510 mm
Pad driver description	Flexible disc w/ centering lock, free floating motor, accommodates uneven floors
Pad speed burnishing	1600 rpm
<b>Chassis/Body Construction</b>	
Handle design	Twist grip operation w/ safety lock; constructed of rotationally-molded polyethylene
<b>Productivity</b>	
Maximum coverage rate per hour	10,000 ft <sup>2</sup> / 929 m <sup>2</sup>
<b>Machine Dimensions</b>	
Length	29.75-inch / 755 mm
Machine Width	20.75-inch / 530 mm
Height	49-inch / 1245 mm
Weight	68 lb / 30.84 kg
<b>Power cord</b>	
Power cord length	75 ft/ 22.85 mm
Power cord type	14 gauge, 3-wire, SJT
<b>Warranty</b>	3 YEARS/2500 HOURS PARTS AND LABOR. NO TRAVEL. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. PLEASE CALL FOR MORE WARRANTY INFORMATION