

Pacesetter™ 17HD/20HD/20SD/20TS

Floor Machines



Typical Applications Include

- Supermarkets
- Schools and Universities
- Hospitals
- Office Buildings
- Hotels / Motels
- Heavy Manufacturing Plants

Optional Accessories Include

- A variety of brushes
- Level-set pad holder
- Splash guard
- Handle-mount solution tank
- Additional weight kit available

Whether stripping, scrubbing, screening, or bonnet cleaning, the Advance Pacesetter™ line of floor machines has a model to fit your needs and applications. Each of the four Pacesetter models is built with an all cast metal, chrome plated base. The heavy-duty construction and durability of the Pacesetter sets it above the competition.

All Pacesetter models have an ergonomic molded handle that protects the user's hands during operation along walls and around corners. A red safety-lock switch allows the operator to easily control when the machine goes into operation. An easy-to-use compression style lever changes the height adjustment of the handle for all operators. Pad holders are standard on the Pacesetter, and the yellow, super-flex cord offers ease in cord handling and reduced tangling. A clear plastic hospital plug allows the operator to verify the electrical integrity of the connection at each use of the machine.

At 1.5 hp, 175 rpm, the **Pacesetter™ HD** is available in 17 and 20 inch sizes. A triple-planetary gear design lasts longer than other gear drives because they do not develop a wear pattern. A sealed gear box requires no maintenance.

The **Pacesetter™ 20SD** is a super duty 20 inch floor machine. For extreme duty, the 1.75 hp, 175 rpm machine also has the triple-planetary gear design for longer wear.

The **Pacesetter™ 20TS** is a two-speed floor machine with a 1.5 hp and a DC rectified motor. The two-speed machine runs at 180 and 320 rpm.

Pacesetter™ 17HD/20HD/20SD/20TS

Floor Machines



Molded, ergonomic handle includes comfortable trigger levers and safety lock-out switch.



Easy to use handle height adjuster.



The 50 foot cord is non-marking safety yellow colored.

- 1 Safety activation switch on all models
- 2 Easy to use compression adjuster for handle height
- 3 Convenient cord wrap holder
- 4 Heavy gauge metal construction throughout base
- 5 Base is cast metal and chrome plated for easy cleanup
- 6 Large non-marking rear wheels make transporting easy

17 in (43 cm) and 20 in (51 cm) pad or brush sizes



Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factory-trained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Parts.

Technical Specifications

| Models | Pacesetter™ 17HD | Pacesetter™ 20HD | Pacesetter™ 20SD | Pacesetter™ 20TS |
|------------------------|---|------------------------------------|--|------------------------------|
| Pad / Brush Size | 17 in (43.2 cm) | 20 in (50.8 cm) | 20 in (50.8 cm) | 20 in (50.8 cm) |
| Pad Drive System | | | | |
| Motor Horsepower | 1.5 hp AC | 1.5 hp AC | 1.75 hp AC | 1.5 hp DC Rectified |
| Frame Size | 66 | 66 | 66 | 66 |
| Motor Amps | 15 A | 15 A | 15 A | 15 A |
| Capacitors | Dual, start and run | Dual, start and run | Dual, start and run | N/A |
| Motor Voltage | 120 V | 120 V | 120 V | 120 V |
| Revolutions Per Minute | 175 rpm | 175 rpm | 175 rpm | 180/320 rpm |
| Transmission | Triple planetary gears – all metal | Triple planetary gears – all metal | Triple planetary gears – all metal gears box | Triple planetary severe duty |
| Clutch Plate | NP 92 (industry standard) | NP 92 (industry standard) | NP 92 (industry standard) | NP 92 (industry standard) |
| Body Construction | All steel with chrome plated bell housing and handle shaft with compression style handle height adjustment. Includes rubber wheels for transportation. – ALL MODELS | | | |
| Machine Weight | 100 lb (45 kg) | 102 lb (46 kg) | 102 lb (46 kg) | 87 lb (40 kg) |
| Power Cord | | | | |
| Length | 50 ft/ 15.25 m – ALL MODELS | | | |
| Type | Safety Yellow Super-flex with hospital grade plug – ALL MODELS | | | |
| Operator Handle | Comfortable and solid handle with safety interlock activation preventing accidental start-up – ALL MODELS | | | |
| Noise Level | 65 dB A | 65 dB A | 65 dB A | 70 dB A |
| Approvals | ETL, CSA | ETL, CSA | ETL, CSA | ETL, CSA |
| Model Numbers | 01330A | 01410A | 01460A | 01440A |

Specifications are subject to change without notice.



Nilfisk, Inc.

9435 Winnetka Avenue North
Brooklyn Park, MN 55445
www.advance-us.com
Phone 800-850-5559
Fax 800-989-6566

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.nilfisk-advance.ca
Phone 800-668-8400
Fax 800-263-5111

 **Advance**
by Nilfisk

