

# Take a walk on the clean side

- automatic scrubbers designed to push productivity



# Floor cleaning will be a walk in the park

The Clarke CA60 series of scrubbers are highly productive with battery and tank capacity to clean for hours. With a working width of 20 inches. and a tank capacity of 16 gallons these machines will get the job done fast and easy. The machines are well balanced and easy to maneuver thanks to large main wheels and strong supporting casters.

- High capacity 16 gallon water and recovery tanks
- On-board charger for convenient battery charging
- Safety switches built into the handle
- Disc version available with or without traction motor
- Orbital versions use less water and chemicals and have the ability to remove floor finish using plain water

For intensive cleaning or maintaining large coated floor areas, the CA60 with orbital scrub deck ensures multi-directional cleaning performance with low solution and detergent consumption and the rectangular deck gives easy to access corners.



Control panel with intuitive display for ease of operation.



Fully accessible recovery tank with debris catch cage allows for simple cleanup.



Orbital technology cleans with multi directional scrubbing action while using less water and chemicals.

## Technical specifications

Description	CA60 20D	CA60 20D	CA60 20DT	CA60 20DT	CA60 20B	CA60 20B	CA60 24B	CA60 24B
Solution/recovery tank	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)	16 Gal. (61L)
Cleaning path	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	20 in. (51cm)	24 in.	24 in.
Brush/pad pressure	60 lbs. (27 kg)	60 lbs. (27 kg)	51 lbs. (23 kg)	51 lbs. (23 kg)	88/110 lbs. (40/50 kg)	88/110 bs. (40/50 kg)	88/110 lbs. (40/50 kg)	88/110 lbs. (40/50 kg)
Squeegee width	30 in. (76cm)	30 in. (76cm)	30 in. (76cm)	30 in. (76cm)	30 in. (76cm)	30 in. (76cm)	30 in. (76cm)	30 in. (76cm)
Sound pressure level	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)	69 +/- 3 dB(A)
Brush speed	150 RPM	150 RPM	150 RPM	150 RPM	2,250 RPM	2,250 RPM	2,250 RPM	2,250 RPM
Brush motor	0.6 HP, 450W	0.6 HP, 450W	0.6 HP, 450W	0.6 HP, 450W	1HP, 750W	1HP, 750W	1HP, 750W	1HP, 750W
Vacuum motor power	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W	.47HP, 350W
Waterlift	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)	47 in. (120cm)
Drive motor	N/A	N/A	.20HP, 150W	.20HP, 150W	.34HP, 250W	.34HP, 250W	.34HP, 250W	.34HP, 250W
Drive type	pad assist	pad assist	traction	traction	traction	traction	traction	traction
Climbing Capacity	2%	2%	2%	2%	2%	2%	2%	2%
Weight no batteries and water	201 lbs. (91 kg)	201 lbs. (91 kg)	214 lbs. (97 kg)	214 lbs. (97 kg)	269 lbs. (122 kg)	269 lbs. (122 kg)	273 lbs. (124 kg)	273 lbs. (124 kg)
Length x Width x Height	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x22x42.5 in. (126x55x108cm)	50x26x42.5 in. (126x65x108cm)	50x21x42.5 in. (124x53x108cm)
Reference	56385411	56385412	56385413	56385415	56385416	56385417	56385418	56385419