

32" Industrial Battery-Operated Floor Scrubber

Kärcher's most powerful walk-behind scrubber









BD 80/120 W Bp



Kärcher's most powerful walk-behind floor scrubber

The BD 80/120 W Bp is Kärcher's largest walk behind floor scrubber and the most efficient machine in its range. The BD 80/120 W handles all cleaning jobs quickly, efficiently and with amazing maneuverability. It's heavy-duty design includes pneumatic tires, an industrial squeegee, 23-gallon solution and 25-gallon recovery tanks to support continuous cleaning of up to 3-hours. The BD 80/120 W also features tool-free, easy access brushes and batteries.





- 1 Significantly restricted line guidance of the casing
- For quick cleaning speeds.
- Allows a clear view of the area to be cleaned.
- 2 Easy access to brushes, batteries and recovery water tank
- Quick maintenance with no tools required.
- The recovery water tank can be easily cleaned.
- Optimum access to the batteries, motors or other components.

Standard Accessories - Brush Configuration

9.840-555.0 Pump Kit with flip tool, hose assembly and coupler (field installation required)

Order No.	Description	
8.600-033.0	Brush, 16" Mild Grit, Blue with Wear Indicators	
8.600-753.0	Skirt, Scrub Deck, Left Side	
8.600-754.0	Skirt, Scrub Deck, Right Side	
8.600-143.0	Blade, AQ, Left, 16"	
8.600-142.0	Blade, AQ, Right, 16"	
8.600-749.0	Squeegee, Rear Blade, Linatex	
8.600-983.0	Squeegee, Front Blade, Linatex	
Optional Accessories - Brush Configuration		
8.600-031.0	Brush, 16" Nylon, Scrub, with Wear Indicators (field installation required)	
8.600-032.0	Brush, 16" Nylon Polishing, White with Wear Indicators (field installation required)	
8.600-033.0	Brush, 16" Mid-grit with Wear Indicators (field installation required)	
8.600-034.0	Brush, 16" Super Aggressive, Grey with Wear Indicators (field installation required)	
8.613-704.0	Squeegee, Rear Blade, Urethane (field installation required)	
8.613-705.0	Squeegee, Front Blade, Urethane (field installation required)	
8.613-516.0	Blade, Aqua-Mizer TM , Left, Urethane (field installation required)	
8.613-517.0	Blade, Aqua-Mizer™, Right, Urethane (field installation required)	
8.609-064.0	Wheel Assembly, 12" Non-Marking (2 required) (field installation required)	
8.613-741.0	Wheel Assembly, 12" Solid Rubber (2 required) (field installation required)	
9.840-549.0	Emergency Shut-off Kit (field installation required)	



Technical data

	BD 80/120 W Bp (Brush Configuration)	BD 80/120 W Bp (Pad Configuration)
	Includes curved vacuum barClearly arranged and flexibleRugged industrial machines	
Technical data		
Brush working width	32" (813 mm)	32" (813 mm)
Working width, vacuum	40" (1,016 mm)	40" (1,016 mm)
Fresh/recovered water tank	23 gallon / 25 gallon (87 / 95 l)	23 gallon / 25 gallon (87 / 95 l)
Practical working capacity	28,800 f ² /h (2,675 m ² /h)	28,800 f²/h (2,675 m²/h)
Pad rotation speed	200 rpm	200 rpm
Brush contact pressure	0 - 150 psi	0 - 150 psi
Battery	36 V	36 V
Weight	375 lbs (170 kg)	375 lbs (170 kg)
Dimensions (L x W x H)	62" x 24" x 45" (1800 mm x 710 mm x 1170 mm)	62" x 24" x 45" (1800 mm x 710 mm x 1170 mm)
	·	
Equipment		
Roller brush	-	-
Disc brush	•	•
Traction drive		
2-tank system	•	•
Curved vacuum bar		
Battery included	$\square / \blacksquare^{1)} / \blacksquare^{2)} / \blacksquare^{3)} / \blacksquare^{4)}$	$\square / \blacksquare^{1)} / \blacksquare^{2)} / \blacksquare^{3)} / \blacksquare^{4)}$
Order No.	9.840-732.0/-733.0/-734.0/-735.0/-736.0	9.840-822.0/-823.0/-824.0/-825.0/-826.0

[■] Included in delivery. ☐ Optional. ¹) 260 Ah, low-maintenance ²) 330 Ah, low-maintenance ³) 335 Ah, low-maintenance ⁴) 312 Ah, AGM

Standard Accessories - Pad Configuration

Order No.	Description	
8.600-029.0	Pad Driver, 16" SD	
8.600-507.0	Lock, Pad Center Snap, Two Step	
8.600-753.0	Skirt, Scrub Deck, Left Side	
8.600-754.0	Skirt, Scrub Deck, Right Side	
8.600-143.0	Blade, Aqua-Mizer™, Left, 16"	
8.600-142.0	Blade, Aqua-Mizer™, Right, 16"	
8.600-749.0	Squeegee, Rear Blade, Linatex	
8.600-983.0	Squeegee, Front Blade, Linatex	
Optional Accessories - Pad Configuration		
8.613-704.0	Squeegee, Rear Blade, Urethane (field installation required)	
8.613-705.0	Squeegee, Front Blade, Urethane (field installation required)	
8.613-516.0	Left Scrub Deck Skirt, oil resistant polyurethane (field installation required)	
8.613-517.0	Right Scrub Deck Skirt, oil resistant polyurethane (field installation required)	
8.609-064.0	Wheel Assembly, 12" Non-Marking (2 required) (field installation required)	
8.613-741.0	Wheel Assembly, 12" Solid Rubber (2 required) (field installation required)	
9.840-549.0	Emergency Shut-off Kit (field installation required)	
9.840-555.0	Pump Kit with flip tool, hose assembly and coupler (field installation required)	



Your Authorized Kärcher Floor Care Dealer:

Kärcher Commercial Phone 888-805-9852 Fax 800-248-8409 info@karchercommercial.com www.karchercommercial.com