KÄRCHER

makes a difference









ROBUST, RELIABLE AND POWERFUL

These high-performing wet/dry vacs feature HEPA standard, better filter cleaning technology and they are even more robust.

We make the system. They make the attachments.

At Kärcher, we are concerned about your health and safety. We think that it is important to get the vacuum system down perfectly first. Our competition only seems to be concerned with the tool attachments.

The new generation of Tact wet and dry vacuums are high-performing units that pack a lot of features. Thanks to our continuous improvements to our automatic cleaning system (Tact), large amounts of fine dusts can be vacuumed without any interruption in suction. Vacuum performance remains at the same high level you have come to expect from Kärcher wet/dry vacs. There is no need of manual filter cleaning. It is fully compliant with the new OSHA silica dust regulations. The perfect solution for demanding customers in the rental, construction, industrial and automotive industries. We make the best wet and dry vacuum cleaner in the market!











1 Filtration System

- Improved Tact automatic filter cleaning system-improved cleaning performance and reduced noise level
- Fully compliant with the new OSHA silica dust regulations
- HEPA filter is standard with NT 30/1, NT 40/1 & NT 50/1

2 Robust Design

- Even stronger and sturdier components and overall design
- Large metal caster wheels for easier usage at construction sites

Improved Accessories on NT 30/1, NT 40/1 & NT 50/1

- Accessory system improves performance and usability
- Bayonet and clip connections guarantee easy and secure connection of all accessory parts onto machine
- The new bend with rubber grip area has an ergonomic design for comfortable working conditions.

4 Easier to Use NT 30/1, NT 40/1 & NT 50/1

- Easy handling: EASY! Operation Switch, integrated accessory storage
- Large net volume and easy handling thanks to convenient location of vacuum hose connector
- Flat vacuum head with power tool box fixation options
- Wider inner diameter of vacuum hoses 1-3/8 inches (DN 35) standard

Technical specifications and order numbers.

	NT 30/1 TACT TE	NT 40/1 TACT TE	NT 50/1 TACT TE	NT 65/2 TACT
TECHNICAL SPECIFICATIONS				
Air flow rate cfm	150	150	150	280
Water lift in	102	102	102	88
Container capacity ga	8.2	10.3	13.5	17.2
Max. power rating W	1380	1380	1380	1800
Sound pressure level dBA	68	68	68	73
Weight lbs	30.0	32	40	54
Cord length f	25	25	25	33
Vac hose	1-3/8" x 13 ft	1-3/8" x 13 ft	1-3/8" x 13 ft	1-5/8" x 13 ft
Dimensions (L x W x H) ir	22 x 14.5 x 22.2	22 x 14.5 x 25.7	25.1 x 14.5 x 41.1	22 x 19.5 x 34.5

EQUIPMENT

Order No.	Item Description
1.148-216.0	NT 30/1 Tact Te
1.148-316.0	NT 40/1 Tact Te
1.148-416.0	NT 50/1 Tact Te
1.667-310.0	NT 65/2 Tact ²

1.6	57-310.0	NT 65/2 Tact ²
AC	CESSORIES	
	Order No.	Item Description
•	2.889-192.0	Stainless steel vacuum tube set
•	2.889-135.0	Vacuum hose 13 ft (Te versions)
•	2.889-134.0	Vacuum hose 8 ft (30/1 Tact L)
-	2.889-170.0	Ergonomic bend
•	2.889-152.0	Wet and dry floor nozzle
-	2.889-159.0	Crevice nozzle
•	2.889-151.0	Power tool adaptor (Te versions)
-	2.889-154.0	Fleece filter bags 30 l for both 30/1 models
•	2.889-155.0	Fleece filter bags for 40/1 & 50/1
-	6.907-629.0	Hepa filter (included with NT 30/1, NT 40/1, NT 50/1)
	2.889-137.0	Vacuum hose 1-3/8 inch diameter (DN 35) 13 ft electrically conductive
	2.889-136.0	Vacuum hose 1-3/8 inch diameter (DN 35) 8 ft electrically conductive
	2.889-164.0	Vacuum hose 1-3/8 inch diameter (DN 35) 8 ft heat-resistant
	2.889-172.0	Ergonomic bend 1-3/8 inch diameter (DN 35) with soft grip electrically conductive
	2.889-148.0	Ergonomic bend 1-3/8 inch diameter (DN 35) with soft grip and vacuum power regulation
	6.907-455.0	Flat pleated filter PTFE
	2.679-000.0	Drilling dust nozzle 1-3/8 inch diameter (DN 35)
	2.643-868.0	Push handle for NT 40/1 Tact Te L
	2.889-138.0	Vacuum hose 1-5/8 inch diameter (DN 40), 13 ft
	2.889-139.0	Vacuum hose 1-5/8 inch diameter (DN 40), 8 ft
	2.889-141.0	Vacuum hose 1-5/8 inch diameter (DN 40), 13 ft electrically conductive
	2.889-140.0	Vacuum hose 1-5/8 inch diameter (DN 40), 13 ft oil-resistant
	2.889-171.0	Ergonomic bend 1-5/8 inch diameter (DN 40), with soft grip
	2.889-172.0	Ergonomic bend 1-5/8 inch diameter (DN 40), with soft grip electrically conductive
	2.889-194.0	Set of vacuum tubes 1-5/8 inch diameter (DN 40), 2 x 1.8 ft, stainless steel
	6.907-629.0	HEPA filter for NT 30/1, NT 40/1 & NT 50/1
	2.889-174.0	Wide wet and dry floor nozzle with easily changeable inserts for wet/dry applications
	5.032-427.0	Elbow Tube 40mm (for NT 65/2 Tact)
	6.906-321.0	Suction hose 40 mm (for NT 65/2 Tact)
	6.904-285.0	5 Pk Paper Filter Bags NT 65/2 (for NT 65/2 Tact)
	6.907-276.0	Flat Pleated Filter (for NT 65/2 Tact)
	6.904-364.0	HEPA Filter (for NT 65/2 Tact)
	5.453-016.0	Power Tool Adapter 35mm Fem. thread - Bulk Pack (for NT 65/2 Tact)
	6.900-275.0	Metal Suction Tube 40mm - Bulk Pack (for NT 65/2 Tact)
	6.903-033.0	Crevice Tool 40mm - Bulk Pack (for NT 65/2 Tact)
	2.639-873.0	Hose Coupler 40mm - Bulk Pack (for NT 65/2 Tact)
	5.407-108.0	Reducer Sleeve 40mm to 35mm male thread Bulk Pack (for NT 65/2 Tact)
	6.907-408.0	Floor Nozzle - 40mm - Bulk Pack (for NT 65/2 Tact)
	5.453-042.0	(Photo 1 below) Power tool adapter, fits these size shrouds: 1.06" - 1.10" OD, 1.25" - 1.32" OD, 1.37" - 1.44" OD, 1.47" - 1.50" OD
	5.453-016.0	(Photo 2 below) Power tool adapter, fits these size shrouds: 1.06" - 1.07" OD, 1.27" - 1.30" OD, 1.40" - 1.41" OD
	5.407-108.0	(Photo 3 below) Power tool adapter: connects to 40mm hose connection, screws into 35mm hose or 5.453-016.0 tool adapter
	2.637-217.0	(Photo 4 below) Power tool "Y" adapter
	5.453-085.0	(Photo 5 below) Power tool adapter sleeve 40 x 50 mm
	5.031-703.0	Tension ring (order with 5.407-113.0)
	5.407-113.0	(Photo 6 below) Reducer, DN 40 to DN 35 hose connection

■ Included □ Optional













Please contact us for more information:

North America Headquarters

4555 Airport Way Denver, CO 80239 U.S.A.

Camas, WA

4275 NW Pacific Rim Blvd Camas, WA 98607 U.S.A.

Phone +1 800 771-1881 Fax +1 877 526-3246

www.karcher.com/us www.sharkpw.com