Vario Automatic Scrubbers TTV 678 Ride-on Scrubber

With three adjustable scrubbing widths (26", 30" and 34") and onboard storage for two squeegees (30" and 40"), simply pull a pin and the brush deck automatically adjusts in or out to the right width for the job.

Key Features

- Fits through almost any door to handle jobs large or small
- · Three sizes in one machine
- Fully adjustable flow rate from 0.25 gpm to 1 gpm
- 4 hours of run time powered by 6 maintenance-free gel batteries
- Easy change patented pop-on/pop-off brushes and pad drivers
- LED control panel provides continuous chemical, water flow, brush pressure and battery status
- · Adjustable brush pressure and speed
- · Prolonged battery life with low-voltage shutoff
- Proper chemical use with onboard dispensing system, allowing for 32:1, 64:1, 96:1 and 128:1 dilutions
- Tear-away squeegee with quick-release blades for easy cleaning
- Optional off aisle kit that can be stored on the machine

Gel Batteries:

- · Safest, most dependable batteries on the market
- · Longest-life batteries on the market
- Emit 1/40 of the hydrogen gas of wet lead acid batteries
- · Spill-proof and can be charged anywhere



TTV 678

MODEL TTV 678

| Cleaning Path | 26", 30", 34" |
|------------------------|-------------------------|
| Pad or Brush Size | 3" x 12" |
| Solution/Recovery Tank | 32 gal. |
| Chemical Capacity | 1 gal. |
| Chemical Mixture Rates | 32:1, 64:1, 96:1, 128:1 |
| Water Flow Rate | 0.25, 0.5, 0.8, 1.0 gpm |
| Brush Pressure | 160 lb max |
| Brush Speed | 125–200 rpm |
| Brush Motor | 3 x 24 V, 400 W |
| Traction Motor | 600 W |

| Maximum Gradient |
|--------------------------------|
| Working Speed |
| Vacuum Motor Power |
| Noise Level dB(A) |
| Working Capacity (sq. ft./hr.) |
| Run Time |
| Batteries (Gel) |
| Weight (Including Batteries) |
| Dimensions (LxWxH) |

| 11° |
|-------------------|
| 0.3-4.3 mph |
| 24 V, 400 W |
| 69 dB(A) |
| 40,200 - 52,500 |
| 4 hours |
| 6 x 12V, 100 Ahr. |
| 1,100 lb |
| 66" x 26" x 56" |
| |