

TASKI® swingo® 2500 and 3500

Battery-powered ride-on auto scrubber



TASKI swingo 2500 displayed

Key Features

- ▶ Unbeatable cleaning performance
- ▶ Unique ergonomics
- ▶ Reliability and durability
- ▶ Unrivalled productivity

Unbeatable cleaning performance

- ▶ A patented all wheel steering system defines new standards in maneuverability; allowing the use of this ride-on machine even in narrow and congested areas. The innovative squeegee concept ensures a 100 percent edge-to-edge water pick-up even in curves and while turning.

Unique ergonomics

- ▶ The machine offers a seated operating position coupled with a high working speed. The extremely low noise level, which is comparable to the noise level of a vacuum cleaner, makes work more enjoyable and allows for day cleaning.

Reliability and durability

- ▶ Fewer mechanical parts and a robust construction makes this machine very reliable. Easily exchangeable brushes and squeegee blades allow simple maintenance and ensures the machine can be easily prepared for use at any time.

Unrivalled productivity

- ▶ A higher cleaning speed of 5 mph (8 km/h) combined with the patented CSD system make the TASKI swingo 2500 and 3500 ride-on auto scrubber series 40 percent more productive compared to walk-behind auto scrubbers.



TASKI swingo 2500 and 3500 Specifications

TASKI swingo 2500 and 3500 Technical Data

Description	swingo 2500	swingo 3500	Description	swingo 2500	swingo 3500
Practical performance	56,500 ft ² /h (5,250 m ² /h)	64,000 ft ² /h (5,950 m ² /h)	Machine weight ready for use (w/o driver)	1,235 lbs (560 kg)	1,257 (570 kg)
Working width	28 inch (70 cm)	33 inch (85 cm)	Dimensions (L x W x H) (w/o squeegee)	31 x 67 x 54 inches (78 x 169 x 137 cm)	36 x 67 x 54 inches (91 x 169 x 137 cm)
Squeegee width	37 inch (93 cm)	43 inch (108 cm)	Brush pressure (maximum)	115-163 lbs (52-74 kg)	132-225 lbs (60-102 kg)
Solution tank-bag system (nominal)	25 gallons (95 l)	25 gallons (95 l)	Cleaning speed	5 mph (8 km/h)	5 mph (8 km/h)
Recovery tank-bag system (nominal)	25 gallons (95 l)	25 gallons (95 l)	Transportation speed	6 mph (9.0 km/h)	6 mph (9.0 km/h)
Rated voltage	24 V	24 V	Sound level	67 dB(A)	67 dB(A)
Nominal consumption	2,000 W	2,000 W	Turning circle	7 feet (2 m)	7 feet (2 m)
Battery capacity (max)	240-290 Ah/C5	240-290 Ah/C5			
Battery run time (nominal)	3-5 h	3-5 h			

TASKI swingo 2500 and 3500

Model	SKU Number
TASKI swingo 2500	8004.741
TASKI swingo 3500	8004.751

Accessories/Additional Parts

Description	SKU Number
Drive discs 14/17 inch (35/43 cm) TASKI swingo 2500/3500	8501.120/8501.130
Hard nylon brush 14/17 inch (35/43 cm) TASKI swingo 2500/3500	8501.080/8505.100
Wash concrete brush 14/17 inch (35/43 cm) TASKI swingo 2500/3500	8501.060/8501.090
Pro-grit abrasive brush 14/17 inch (35/43 cm) TASKI swingo 2500/3500	8502.917/8501.919

Description of Features

CSD (Cleaning Solution Dosing): The CSD system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50 percent saving in cleaning solution, leading to significantly increased productivity of the machine.