

TASKI® swingo® XP

Stand on 30-inch (75-cm) auto scrubbers



Key Features

- ▶ Greatly increased productivity
- ▶ Best cleaning results
- ▶ Immediately dry floors
- ▶ Reduced water and energy consumption

Greatly increased productivity

- ▶ The new stand-on concept with sensor steering combines excellent manoeuvrability with speed for faster cleaning. A highly efficient water management system reduces the number of time-consuming tank filling stops.

Highest cleaning results

- ▶ The new scrubbing unit with micro-rotating movement offers high level cleaning results, while saving up to 50 percent of the cleaning solution versus conventional rotary or cylindrical systems.

Immediately dry floors

- ▶ The excellent drying result (due to the W-shaped squeegee) allows use of the machine at any time of the day, while reducing the potential risk of slip-fall accidents caused by wet floors.

Reduced water and energy consumption

- ▶ The environmentally-friendly machine leads to more efficient use of natural resources.
-

TASKI swingoXP Specifications

TASKI swingo XP Technical Data

| Description | | Description | |
|--------------------------|---|---|---|
| Practical performance | 24,200 ft ² /h (2,250 m ² /h) | Machine weight ready for use (w/o driver) | 905 lbs (410 kg) |
| Working width | 32 inch (81 cm) | Dimensions (L x W x H) | 47 x 37 x 50 inches (119 x 95 x 126 cm) |
| Squeegee width | 37 inch (94 cm) | Door pass through width (w/o squeegee) | 32 inch (81 cm) |
| Solution tank-bag system | 28 gallons (105 l) | Brush system | 2 units 18 x 6 inches (45 x 15 cm) |
| Recovery tank | 28 gallons (105 l) | Micro-rotation speed of brushes | 550 rpm |
| Rated voltage | 24 V | Brush pressure min-max | 35-95 lb. |
| Nominal consumption | 1,200 W | Cleaning speed | 4 mph (6 km/h) |
| Battery capacity (max) | 195 Ah/C5 | Sound level | 65 dB(A) |
| Battery run time | 3.5 h | | |
| Machine weight net | 397 lbs (180 kg) | | |

TASKI swingo XP

| Model | SKU Number |
|-----------------|------------|
| TASKI swingo XP | 7514505 |

Accessories

| Description | SKU Number | Description | SKU Number |
|---------------------------------------|------------|---------------------------------------|------------|
| Scrubbing brush Nylon 450 mm | 7514650 | TASKI s-pad 450 mm Blue (pack of 10) | 7514729 |
| Pad drive harpoon grip 450 mm | 7514648 | TASKI s-pad 450 mm Brown (pack of 10) | 7514730 |
| TASKI contact pad 450 mm (pack of 4) | 7514732 | TASKI s-pad 450 mm Black (pack of 10) | 7514731 |
| TASKI s-pad 450 mm White (pack of 10) | 7514727 | Battery - 6V, 175 Ah, 4 req'd | 5048062 |
| TASKI s-pad 450 mm Red (pack of 10) | 7514728 | | |

Description of Features

BMS (Battery Management System): An internal monitoring system prevents deep discharging of the batteries. LED Battery display allows the operator to visually check condition of battery charge.

CSD (Cleaning Solution Dosing): The CSD system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50 percent saving in cleaning solution, leading to significantly increased productivity of the machine.

Micro rotating scrub deck: Combines the best attributes of rotary and cylindrical cleaning all in one patented scrubbing platform. No need to choose one or the other.

Patented squeegee: The unique "W" shape with dual pickup hoses continuously self-adjusts to the flooring surfaces and delivers a dry floor without "trail mopping." Easy on/off squeegee.