

Commercial Floor Care Equipment

3500/3520 Wet Dry Vacuum



Features	Specifications	
Product Name Model Number	3500 607673	3520 607674
Chassis/Body Construction		
Caster Diameter	Rotationally-molded polyethylene	Rotationally-molded polyethylene
Wheel Diameter	4 in/ 10 cm	4 in/ 10 cm
	10 in/ 25 cm	10 in/ 25 cm
Vacuum Recovery System		
Airflow at Orifice	$103 \text{ cfm}/2.9 \text{ m}^3/\text{hr}$	$100 \text{ cfm}/ 2.9 \text{ m}^3/\text{hr}$
Water lift at Sealed Orifice:	92 in/ 233 cm	120 in/ 233 cm
Vacuum Motor Horsepower:	1.3 hp	1.6 hp
Vacuum Motor Amps:	8.5 Å	10.7 Å
Vacuum Motor Diameter:	5.7 in/ 14 cm	5.7 in/ 14 cm
Vacuum Motor Stages:	2 Stage	3 Stage
Vacuum Motor Voltage:	120 V	120 V
Vacuum Motor Watts:	980 Watts	1242 Watts
Recovery Tank Capacity:	15 gal/ 56 L	15 gal/ 56 L
Vacuum Bag Capacity:	1/3 bushel/ L	1/3 bushel/ 10 L
Dimensions		
Product Height:	37.5 in/ 95 cm	37.5 in/ 95 cm
Product Length:	29 in/ 73 cm	29 in/ 73 cm
Product Width:	15.5 in/ 39 cm	15.5 in/ 39 cm
Product Weight:	44 lb/ 20 kg	44 lb/ 20 kg
Power Cord		
Power Cord Length	50 ft/ 15 m	50 ft/ 15 m
Accessories/Tools Standard	10 ft x 1.5 in/2 cm x 3 cm vacuum hose, standard drain hose. One cloth and one paper filter bag.	
	Contractor tool kit: Dual bend aluminum wand.	
Optional Accessories	The 26 in/ 66 cm, 33 in/ 83 cm, or 39 in/ 99 cm	
· · · · · · · · · · · · · · · · · · ·	Squeegee Attachment Kit.	



Warranty	Tennant warrants the rotationally-molded polyethylene housings and parts on all of its machines to	
	be free from defects in materials and workmanship, under normal use and service for ten (10) years	
	to the original end user. Under this warranty, we guarantee the performance of non-polyethylene	
	parts and components to be free from defects for up to three (3) years or 2,500 hours of operation,	
	whichever comes first, to the original end user. Parts replaced or repaired under this warranty are guaranteed for the remainder of the original warranty period. Labor charges are covered for three	
	(3) full years form the date of purchase for Tennant models, provided an authorized Tennant	
	service provider is used for repair.	

