



# **T391**

## Mid-Size Walk-Behind Scrubber

#### **Productive and Easy to Operate**

The T391 provides a reliable and productive cleaning experience. Clean more efficiently with the wide scrub head and large tank capacity; featuring a simple control panel, comfortable ergonomics, and straight-forward operation.

#### Available technologies



ec-H2O NanoClean® technology



**Comfortable & Easy to Maneuver** Maximize operator comfort with great maneuverability and adjustable controls.



A Reliable Clean Optimize cleaning performance and efficiency with self-leveling scrub head and self-propel drive.



**Productivity Boost** Get more cleaning done compared to smaller scrubbers with wide scrub path and large solution tank capacity.

### Inside the T391

- Simplified operator training with easy-touse pre-programmed cleaning settings.
- 2. Monitor helpful machine information with intuitive and large LCD display that features 13 languages.
- 3. Simple daily maintenance with large sized recovery tank opening enabling full access and visibility.
- Help keep floors dry by recovering water pickup with 2-stage vacuum motor and standard Linatex<sup>®</sup> blades.
- 5. Simple no-tools, no-touch brush/pad change system.
- Easy daily maintenance with yellow touch points to help reduce breakdowns.



## T391 Specifications

FEATURE	SPECIF	SPECIFICATION	
Cleaning path	28 in / 700 mm	32 in / 800 mm	
Productivity (per hour) theoretical max	40,139 ft²/hr / 3,729 m²/hr	47,953 ft²/hr / 4,455 m²/hr	
Maximum speed	4.3 mph / 6.9 kph		
Scrub head raise/lower	manual		
Brush/pad speed	220 rpm		
Brush/pad pressure	52 lbs / 23.6 kg	71 lbs / 32.2 kg	
Solution tank capacity	18.5 gal / 70 L		
Recovery tank capacity	18.5 gal / 70 L		
Battery run time - up-to hours*	3 hrs		
Battery voltage	24 volt		
Dimensions (L x W x H)	51.1 x 33.2 x 40.7 in / 1,298 x 843 x 1,034 mm	52.2 x 33.2 x 40.7 / 1,326 x 843 x 1,034 mm	
Squeegee width	33.2 in /	33.2 in / 843.3 mm	
Weight (with heaviest battery)	388.5 lbs / 176.2 kg	419.3 lbs / 190.2 kg	
Sound level in ECO mode (operator's ear)**	56 dB		

Specifications subject to change without notice. \* Run times are based on Continuous Scrubbing Run Times.

\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

## For a demonstration or additional information, call **+1.800.553.8033** or email **info@tennantco.com**

t391-brochure-en-noam 9/23 ©2023 The Tennant Company. LINATEX and the Linatex red color are trademarks and/or registered trademarks in the name of Linatex Ltd, a Weir Group PLC company. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved. **Tennant Company** 

10400 Clean Street Eden Prairie, MN 55344-2650, USA

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315 www.tennantco.com | info@tennantco.com

Manufacturer PDF Provided by www.southeasternequipment.net