



## Model 3260 Specifications

### WIDE AREA VACUUM

Feature	English / Metric
<b>Brush Drive System</b>	
Brush bristle diameter	0.008-inch/ 0.20 mm
Brush bristle length	5-inch/ 127 mm
Brush design description	Double bristle row, ABS core; spiral patterned
Brush diameter	2.5-inch/ 65 mm
Brush length	24-inch/ 610 mm
Brush motor amps	1 A
Brush motor power	0.2 hp/ 0.15 kW
Brush motor RPM	1800 rpm
Brush motor type	Permanent magnet DC, circuit breaker protected
Brush motor voltage	120 V
Brush RPM	1200 rpm
<b>Vacuum System</b>	
Airflow at orifice	101 cfm/ 2.86 m <sup>3</sup> /h
Waterlift at orifice	114-inch/ 2895 mm
Vacuum motor amps	10 A
Vacuum motor diameter	5.7-inch/ 145 mm
Vacuum motor power	1.57 hp/ 1.17 kW
Vacuum motor stages	2 stage
Vacuum motor voltage	120 V
Vacuum motor type	Thru-flow, thermally protected w/ auto reset, UL recognized
<b>Dirt/Debris Recovery System</b>	
Vacuum bag description	99.9% efficiency for particles of .3 micron
Vacuum bag filtration description	Optional Clean Air Exhaust Filter-99% efficiency at 0.3 microns. Capacity: 1/3 bushel/ 10L. Optional cloth bag available-98% efficiency at 0.3 microns.
<b>Machine Dimensions</b>	
Length	19-inch/ 480 mm
Machine Width	26-inch/ 660 mm
Height	44-inch/ 1117 mm
Weight	44 lb/ 19.96 kg
<b>Chassis/Body Construction</b>	
Chassis construction	Rotationally-molded polyethylene
Metal parts coating	Zinc & chrome plating, epoxy powder coat
<b>Power Cord</b>	
Power cord length	50 ft/ 15.24 m
Power cord type	16 gauge, 3-wire, SJTO, non-marking safety yellow w/ grounded plug. Recognized by UL
<b>Power Consumption</b>	
Power consumption amps	11 A
Power consumption voltage & watts	120 V, 1320 watts
<b>Decibel Rating</b>	
Ten foot/ 3 m decibel	66 dBa
Five foot/ 1.5 m decibel	68 dBa
Operator position	73 dBa