









## PRODUCTIVE. CLEAN. SAFE.

- ▶ Reduce downtime, service time, and maintenance costs by quickly accessing the heart of the M30 with EasyOpen™ service access.
- ▶ Achieve outstanding results in the harshest environments with dual cylindrical brushes combined with a large 95 gal / 360 L recovery tank and 7 ft<sup>3</sup> / 198 L hopper that allows you to sweep and/or scrub in a single pass.
- ▶ Maintain safety and improve efficiency for operators and your facility with the outstanding visibility and ergonomics designed into the ErgoSpace™ operator compartment.



**800.440.6723 • [www.southeasternequipment.net](http://www.southeasternequipment.net)**

### KEY AVAILABLE FEATURES

Increase productivity up to 3 hours. Dramatically extend cleaning time, even when cleaning porous concrete, by continually filtering and recycling recovered solution with the ES® system.

Widen cleaning path from 48 up to 64 inches / 1,220 to 1,625 mm. Achieve impressive edge-cleaning capabilities and maximum productivity with the side brush.

Enhance cleaning flexibility. Blast clean hard-to-reach areas easily with the 25 ft / 7.6 m, 2200 psi pressure washer.

Protect operator and machine. Ensure safety in severe environments with heated and cooled soft cab.



## ENVIRONMENTAL STEWARDSHIP



**ec-H2O™ and FaST® technologies are NFSI (National Floor Safety Institute) Certified.** NFSI certified products must pass a 2-phase wet slip resistance process and have been shown to reduce the potential for slip-and-fall accidents.



**ec-H2O and FaST technologies are registered by NSF International.** NSF International is an independent, not-for-profit organization that ensures formulation and labels on these products meet appropriate food safety regulations.



**ec-H2O and FaST technologies may contribute to LEED or LEED-EBOM (Existing Building: Operations & Maintenance) points,** provided other appropriate criteria are met. For more information on obtaining LEED points, please contact your sales rep or refer to the USGBC website at: [www.usgbc.org](http://www.usgbc.org).



**FaST is a Green Seal (GS-37) Certified Detergent.** Green Seal evaluates and certifies cleaning products based on criteria such as the toxicity of the product, skin and eye irritation, skin sensitization, combustibility, toxicity to aquatic life, and packaging.



Conserve Resources



Reduce Detergents



Increase Safety



Improve Air Quality



Reduce Noise

Choose GE Capital or U.S. Bancorp, our leasing providers, for simple, quick financing with flexible upgrade options.

## M30 RIDER SCRUBBER-SWEEPER

### INTEGRATED CLEANING SYSTEM

Cleaning path	48 in / 1,220 mm
With scrubbing side brush	62 in / 1,575 mm
With sweeping side brush	64 in / 1,625 mm
Cylindrical main brushes	
Brush speed	480 rpm / 480 rpm
Brush down pressure (up to)	390 lb / 177 kg
Brush diameter (2)	12 in / 305 mm
Side brush	
Brush speed	150 rpm / 150 rpm
Scrubbing brush diameter	16 in / 410 mm
Sweeping brush diameter	21 in / 535 mm
Tanks	
Solution tank	75 gal / 284 L
Solution capacity with ES®	100 gal / 379 L
Recovery tank	95 gal / 360 L
Demisting chamber	20 gal / 76 L
Debris hopper	
Volume capacity	7 ft <sup>3</sup> / 198 L
Weight capacity	650 lb / 295 kg
Dump height (variable to)	60 in / 1,525 mm
Vacuum fans	
Scrubbing fan speed	11,000 rpm / 11,000 rpm
Scrubbing fan water lift	35 in / 890 mm
Sweeping fan speed	6,500 rpm / 6,500 rpm
Sweeping fan airflow	290 cfm / 8.2 m <sup>3</sup> /min

### PROPELLING SYSTEM

Propel speed forward (variable to)	8 mph / 13 km/h
Propel speed reverse (variable to)	3 mph / 4.8 km/h
Engine-gasoline/LPG (2.0 L)	50 hp / 37.2 kW
Engine-diesel turbo (1.5 L)	43 hp / 32 kW
Gradeability	
Transport at gross weight	8.0° / 14%
Working (cleaning)	6.0° / 10%
Ground clearance (transport)	3 in / 80 mm

### DUST CONTROL SYSTEM

Filter system	Synthetic fiber panel
Filter area	78 ft <sup>2</sup> / 7.3 m <sup>2</sup>
Dust filtration (to)	3 microns @ 99% efficiency
Shaker mechanism (automatic)	Timed, beater bar

### MACHINE SPECIFICATIONS

Length	108 in / 2,745 mm
Width	
Frame	58 in / 1,475 mm
Rear squeegee	59 in / 1,500 mm
With side brush	64 in / 1,625 mm
Height	58 in / 1,475 mm
With overhead guard	84 in / 2,135 mm
Weight (empty)	4,000 lb / 1,815 kg
Minimum aisle turn	125 in / 3,175 mm

### WARRANTY

See your local representative for warranty information.

Specifications subject to change without notice.



# 800.440.6723

[www.southeasternequipment.net](http://www.southeasternequipment.net)