

CREATING A CLEANER, SAFER, HEALTHIER WORLD.



M30

LARGE INTEGRATED SCRUBBER-SWEEPER

- Outstanding results in just one pass with integrated cleaning system technology
- Lower Total Cost of Ownership[™] without compromising safety or performance
- Improve productivity with ec-H2O[™] or FaST[®] technology for cleaning three times longer than conventional scrubbing methods



800.440.6723

ELIMINATING THE COMPLEXITY OF TRADITIONAL SWEEPER-SCRUBBERS



A fully-integrated scrubber-sweeper, the M30 is engineered for dependable, industrial-strength cleaning when scrubbing, sweeping or doing both at once.

MAXIMIZE YOUR PRODUCTIVITY

Built with a rugged steel frame, long-lasting Duramer[™] construction, and ISO 9001 certified quality manufacturing, the M30 is a machine you can depend on every day of the week.

DRAMATICALLY LOWER TOTAL COST OF OWNERSHIP

Without compromising safety or performance, we've reduced the total cost of ownership for machines that both scrub and sweep. With two brushes instead of four, EasyOpen[™] service access, and 14% fewer parts, the M30 is one of the most efficient industrial cleaning machines available.

SAFER FOR YOUR OPERATORS, CUSTOMERS, AND EMPLOYEES

Protect your operator, your customers, and your facility with Tennant's exclusive ErgoSpace[™] operator compartment, ec-H2O[™] or FaST[®] scrubbing technology, Hygenic[®] cleanable tanks and Grip-N-Go[™] corner rollers.

800.440.6723 • www.southeasternequipment.net

M30 INTEGRATED SWEEPER-SCRUBBERS



INCREASED SAFETY

- FaST® Foam Scrubbing Technology helps reduce the risk of slip-and fall accidents with NFSI certified detergents
- **ErgoSpace**[™] improves operator visibility and response time to obstacles Thermo-Sentry[™] reduces risk of hopper fires
- Grip-N-Go[™] corner rollers protect your facility and machine
- Underwriters Laboratory (UL) Certified

REDUCED COSTS

- ec-H2O[™] technology reduces training, purchasing, storing, handling, and mixing tasks and costs associated with floor cleaning chemicals
- EasyOpen[™] service access and on-board diagnostics
- SmartRelease[™] break-away squeegees reduce maintenance and replacement parts due to squeegee damage
- MaxPro[™] hydraulic technology reduces component wear

MAXIMUM PRODUCTIVITY

- ES® Extended Scrub metering to avoid detergent overuse and conserve water
- Hygenic® tanks easy visibility to solution and recovery tanks for cleaning and sanitization
- Variable Drain Valves[™] control the flow of water leaving the tanks
- Touch-N-Go[™] intuitive control panel remembers last settings

ADDITIONAL EXCLUSIVE TECHNOLOGIES

All technologies increase scrub time up to three times using a single tank of water.



ec-H2O technology electrically converts water into an innovative cleaning solution that cleans effectively, saves money, improves safety, and reduces environmental impact* compared to daily cleaning floor chemicals and methods.




FaST Foam Scrubbing
Technology uses up to 70% less
water and 90% less chemicals
to improve floor traction as
certified by NFSI, helping
reduce the risk of slip and fall
accidents.



ES Extended Scrubbing productivity enhancement system recycles cleaning chemicals to increase uptime and improve productivity by scrubbing floors using 66% less chemicals than traditional cleaning methods.

INSIDE THE

M30



800.440.6723 • www.southeasternequipment.net

PRODUCTIVE, CLEAN, SAFE,

- Reduce downtime, service time, and maintenance costs by quickly accessing the heart of the M30 with EasyOpen™ service access.
- Achieve outstanding results in the harshest environments with dual cylindrical brushes combined with a large 95 gal / 360 L recovery tank and 7 ft³ / 198 L hopper that allows you to sweep and/or scrub in a single pass.
- Maintain safety and improve efficiency for operators and your facility with the outstanding visibility and ergonomics designed into the ErgoSpace™ operator compartment.







800.440.6723 • www.southeasternequipment.net

Increase productivity up to 3 hours. Dramatically extend cleaning time, even when cleaning porous concrete, by continually filtering and recycling recovered solution with the ES® system.

Widen cleaning path from 48 up to 64 inches / 1,220 to 1,625 mm.
Achieve impressive edgecleaning capabilities and maximum productivity with the side brush.

Enhance cleaning flexibility. Blast clean hardto-reach areas easily with the 25 ft / 7.6 m, 2200 psi pressure washer. Protect operator and machine. Ensure safety in severe environments with heated and cooled soft cab.







ENVIRONMENTAL STEWARDSHIP



ec-H2O™ and FaST® technologies are NFSI (National Floor Safety Institute) Certified. NFSI certified products must pass a 2-phase wet slip resistance process and have been shown to reduce the potential for slip-and-fall accidents.



ec-H2O and FaST technologies are registered by NSF International. NSF International is an independent, not-for-profit organization that ensures formulation and labels on these products meet appropriate food safety regulations.



ec-H2O and FaST technologies may contribute to LEED or **LEED-EBOM (Existing Building:** Operations & Maintenance) points, provided other appropriate criteria are met. For more information on obtaining LEED points, please contact your sales rep or refer to the USGBC website at: www.usgbc.org.



FaST is a Green Seal (GS-37) Certified Detergent. Green Seal evaluates and certifies cleaning products based on criteria such as the toxicity of the product, skin and eye irritation, skin sensitization, combustibility, toxicity to aquatic life, and packaging.













Choose GE Capital or U.S. Bancorp, our leasing providers, for simple, quick financing with flexible upgrade options.

M30 RIDER SCRUBBER-SWEEPER

INTEGRATED CLEANING SYSTEM

Cleaning path	48 in / 1,220 mm
With scrubbing side brush	62 in / 1,575 mm
With sweeping side brush	64 in / 1,625 mm
Cylindrical main brushes	
Brush speed	480 rpm / 480 rpm
Brush down pressure (up to)	390 lb / 177 kg
Brush diameter (2)	12 in / 305 mm
Side brush	
Brush speed	150 rpm / 150 rpm
Scrubbing brush diameter	16 in / 410 mm
Sweeping brush diameter	21 in / 535 mm
Tanks	
Solution tank	75 gal / 284 L
Solution capacity with ES®	100 gal / 379 L
Recovery tank	95 gal / 360 L
Demisting chamber	20 gal / 76 L
Debris hopper	
Volume capacity	7 ft ³ / 198 L
Weight capacity	650 lb / 295 kg
Dump height (variable to)	60 in / 1,525 mm
Vacuum fans	
Scrubbing fan speed	11,000 rpm / 11,000 rpm
Scrubbing fan water lift	35 in / 890 mm
Sweeping fan speed	6,500 rpm / 6,500 rpm

Sweeping fan airflow PROPELLING SYSTEM

Propel speed forward (variable to)	8 mph / 13 km/h
Propel speed reverse (variable to)	3 mph / 4.8 km/h
Engine-gasoline/LPG (2.0 L)	50 hp / 37.2 kW
Engine-diesel turbo (1.5 L)	43 hp / 32 kW
Gradeability	•
Transport at gross weight	8.0° / 14%
Working (cleaning)	6.0° / 10%
Ground clearance (transport)	3 in / 80 mm

290 cfm / 8.2 m3/min

DUST CONTROL SYSTEM

Filter system	Synthetic fiber panel
Filter area	78 ft ² / 7.3 m ²
Dust filtration (to)	3 microns @ 99% efficiency
Shaker mechanism (automatic)	Timed, beater bar

MACHINE SPECIFICATIONS

Length	108 in / 2,745 mm
Width	
Frame	58 in / 1,475 mm
Rear squeegee	59 in / 1,500 mm
With side brush	64 in / 1,625 mm
Height	58 in / 1,475 mm
With overhead guard	84 in / 2,135 mm
Weight (empty)	4,000 lb / 1,815 kg
Minimum aisle turn	125 in / 3,175 mm

WARRANTY

See your local representative for warranty information.

Specifications subject to change without notice.

