Industrial Dual-Surface Cleaner

Tor-rent (tôr'ent) - A violently fast stream of water (or other liquid). "The tile and grout was cleaned by a torrent of water".

When cleaning tile and grout, you need a machine that can stand up to long hours and demanding environments. The Torrent has been specifically engineered for just such environments. Equipped with an HT Technology Triplex Plunger Pump, the Torrent can withstand water temperatures up to 185° F and needs no standard service on the pump seals until 3,000 hours. This industrial strength pump has run-dry-seal capability and is adjustable from 400-1200 psi, giving the operator the versatility and power they need for tile & grout hard surface cleaning or carpet extraction. Direct water feed increases production by eliminating the need to stop working and fill a solution tank. Automatic waste water dump keeps the recovery tank empty at 2.5 gallons per minute through a standard 3/4" garden hose, also increasing production. Other innovations included the dual, top-mounted three-stage vacuums that have increased airflow efficiency and dramatically increased water recovery. This means floors will dry quicker and rooms can be put back into use with minimal downtime. With a new upright,



Compact design to easily fit into vehicle or storage

Amp Meter

P

R

0

Dual 3-stage vacuums located on top of the machine for efficient airflow and maximum water recovery



Direct Water Feed

ergonomic, lightweight design, the Torrent is easy to transport or store by a single person. Large rear wheels and skid bars allow the operator easy travel up or down stairs. Other industrial strength features include the rotationally molded body that comes standard with a lifetime warranty against cracks, dents, and leaks. Additional value added features are the smart circuit locator, amp gauge, wand caddy, hour meter, and multiple stage filtration system.

The Torrent will help increase your productivity and cleaning effectiveness, contact us today for a free demo of this innovative industrial dual-surface machine.

U.S. PRODUCTS
Innovative Cleaning Solutions

The Torrent

Industrial Dual-Surface Cleaner

SPECIFICATIONS:

- Dimensions 25"W x 26"L x 40"T
- Weight 145 lbs.
- 2500 psi (Fully adjustable 1200 400 psi working pressures) HT Technology Triplex Plunger Pump
 - · High Temperature/Run Dry Seal Capability (185 Deg. F.)
 - Extended Service Intervals (up to 3,000 hours)
 - Direct water feed reduces cavitation and possible pump damage, inline filter prevents debris from damaging system
 - · Pressure gauge and amp gauge provided for proper pressure adjustment
- Premium Efficiency "Wattsaver" Totally Enclosed Fan Cooled Motor
 - · 1200 psi @ 2.1 gpm under 15 amps
 - Best class (F) motor windings for longer life
- Vacuum Twin 3-Stage top/parallel mounted "High Flow System"
 - Parallel mounted for high cfm
 - · Unique "Air Horn" vacuum manifold for high efficiency
 - Exhaust diffuser reduces db's for quieter operation
- Auto Dump pump 2.5 gpm continuous operation (Float Controlled)
- 10" wheels positioned to climb stairs. Rear wheels and top of handle form "Skid Rails" for ease of loading
- Filtration System Pre-Filter 800 micron polyester mesh with quick change feature, stainless steel 50 mesh tank filter
- Smart Circuit Locator Locates two seperate circuits to eliminate blown fuses or tripped circuit breakers
- Power Cords Two 25', 12 guage, 3-wire hospital grade plugs
- Power Consumption 15 amps per cord
- Hour meter
- Wand caddy designed for Turbo tool Part # HFT-40
- 1 ½" x 25' vacuum and 25' high pressure hose included
- 50' long x 3/4" diameter direct water feed hose, chemical injection, regulator and back flow prevention included.
- ETL/CSA Certified Optional: Electric Floor Finishing and Cleaning Machines (CSA C22.2 No. 10-1965 R2004) Part Number: TORRENT-CSA









GOLD



Cleans Carpet

Innovative Cleaning Solutions

11015 - 47th Ave. W. Mukilteo, WA 98275 Phone: (425) 322-0133 Toll Free: (800) 257-7982

Toll Free: (425) 322-0133 Toll Free: (800) 257-7982 Fax: (425) 322-0136 Web: usproducts.com





Optional Turbo Hard Surface Tool Part Number HFT-40



Optional Mini Turbo Hard Surface Hand Tool Part # HFT-43