

V-SMU-14 | SINGLE MOTOR UPRIGHT VACUUM



The smart alternative to high priced, unreliable commercial vacuums.

Reduce maintenance costs and downtime

The V-SMU-14 eliminates four key issues that cause vacuums to fail, thus increasing productivity and lowering service costs versus current commercial vacs.

Durable and Affordable

Major components have been proven in commercial applications for over 10 years. This vacuum delivers high value at operating costs up to 58% less than other commercial vacuums.*

Healthy, proven performance

Standard with HEPA 3-stage filtration, the vacuum's cleaning performance is also certified Silver by the Carpet and Rug Institute's (CRI) Seal of Approval program.

*Based on acquisition cost and assumed consumables (60 bags, 1 brush roll and 8 HEPA filters per year).

Key Product Features

- LEED qualifying with CRI SOA Silver Performance and noise levels less than 70 dBA.
- Increase productivity and cleaning coverage with onboard crevice and upholstery tools and up to 30% longer wand reach than competition.
- Easy operator serviceability with no-tool brush and belt replacement.



800.440.6723

www.southeasternequipment.net

V-SMU-14 | SINGLE MOTOR UPRIGHT VACUUM



FEATURES	SPECIFICATIONS*
Product Name	V-SMU-14
Vacuum System Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Vacuum motor watts/amps Water lift at sealed orifice	120 cfm / 3.4 m ³ /m 1.6 hp / 1.19 kW each Single stage, thermal protected, clean air 1200 watts / 10 A 89 in / 2260 mm
Brush Drive System Brush belt description Brush type Brush size Brush height	Round drive belt 12 in / 305 mm metal brush roll with natural bristles 2.25 in / 57 mm in diameter, 12 in / 305 mm length Automatic, self-adjusting
Filtration Triple filtration system Triple filtration description Vacuum bag capacity	Filter bag, vac motor filter, and HEPA filter High efficiency (99.97%) at 0.3 micron Fill design, 3.8 qt / 3.6 L
Electrical Power cord length	50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
Chassis/Body Construction Construction	Injection molded ABS
Accessories Standard	On-board crevice tool, dusting brush with telescopic aluminum wand with 15' reach (4:1 stretch)
Dimensions / Weight / Sound Level Length Width Height Weight Sound level (at operator's ear)	12.5 in / 320 mm 14.75 in / 370 mm 44 in / 1120 mm 16 lb / 7.3 kg < 70 dBA
Approvals	ETL, (US/C)
Warranty	See your sales representative or authorized distributor for complete warranty details.

*Specifications subject to change without notice



800.440.6723

www.southeasternequipment.net