




Commercial Floor Care Equipment



Model 1220 Self-Contained Carpet Extractor

Features	Specifications
Product Name Part Number	1220 607853
Brush Drive System Brush Bristle Length: Brush Bristle Type: Brush Diameter: Brush Length: Brush Motor Amps: Brush Motor RPM: Brush Motor Voltage: Brush Motor Watts: Brush RPM:	.75 in /1.91cm Nylon construction, eight rows of bristles arranged with 5 degree lead spiral 3.375 in /8.75 cm 13.5"/34.3 cm 1 A 1800 rpm 120 V 120 watts 1200 rpm
Chassis/Body Construction Chassis Construction: Metal Parts Coating: Wheel Diameter: Wheel Description:	Rotationally-molded polyethylene Epoxy powder coating; extruded aluminum spray bar is black anodized; other parts are zinc-plated or stainless steel 8 in /20.32 cm 10 in /25.4 cm Non-marking gray tread
Dimensions Product Height: Product Length: Product Weight: Product Width:	34 in /86.36 cm 39 in /99.06 cm 86 lb /39.01 kg 16 in /40.64 cm
Decibel Rating Decibel Rating at 10 ft/3 m Decibel Rating at 5 ft/1.5 m Decibel Rating at machine:	71 dBa 73 dBa 77 dBa
Recovery System Recovery Tank Wet Capacity:	7 gal /26.5 L
Total Power Consumption Amps: Voltage: Watts:	12.7 A 120 V 1524 watts
Solution Delivery System Nominal Solution Flow Rate: Solenoid Valve Description: Solution Capacity: Solution Flow Quantity: Spray Jets Count:	1 gpm /3.78 L/min Electrically operated, provides positive spray shut-off. 7 gal /13.24 L 1 gpm /3.78 L/min 4 - quick disconnect



Vacuum System Airflow At Orifice: Vacuum Motor Amps: Vacuum Motor Horsepower: Vacuum Motor Stages: Vacuum Motor Voltage: Vacuum Motor Watts: Sealed Waterlift	99 ft ³ /2.80m ³ 10.3 A 1.66 hp 3 stage 120 V 1236 watts 117 in /297.18 cm
Pump System Solution Pump Pressure: Solution Pump Amps:	100 lb psi (45.36 kPa) 1 A
Power Cord Power Cord Length: Power Cord Type:	50 ft (15.24 m) 16 gauge
Optional Accessories	Hand tool, upholstery tool, extension solution hose, crevice tool, vacuum hose and floor tools.
Warranty	Tennant warrants the rotationally-molded polyethylene housings and parts on all of its machines to be free from defects in materials and workmanship, under normal use and service for ten (10) years to the original end user. Under this warranty, we guarantee the performance of non-polyethylene parts and components to be free from defects for up to three (3) years or 2,500 hours of operation, whichever comes first, to the original end user. Parts replaced or repaired under this warranty are guaranteed for the remainder of the original warranty period. Labor charges are covered for three (3) full years form the date of purchase for Tennant models, provided an authorized Tennant service provider is used for repair.

1220Extractor

